

2

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 60 FEET. INCREASE S-23 CATS C/D VISIBILITY TO 1 3/8 MILE.

CHART NOTE: FOR INOPERATIVE ODALS, INCREASE S-23 CATS C/D VISIBILITY TO 1 3/8 MILE.

CHART NOTE: FOR INOPERATIVE ODALS, WHEN USING WALNUT RIDGE ALTIMETER SETTING, INCREASE S-23 CATS CATS C/D VISIBILITY TO 1 3/8 MILE.

CITY AND STATE

JONESBORO, AR

ELEVATION: 262

THRE: 259

AIRPORT NAME:

JONESBORO MUNI

FACILITY

IDENTIFIER:

JBR

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 23, AMDT 11, 03/07/2013

SUP:

AMDT: 10

DATED: 02/14/2008