

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 4.22 MILES AFTER OOC NDB					
MARTA/AEX VORTAC 61.53 DME		OOC NDB		105.66 / 24.26				2000		CLIMB TO 1000 THEN CLIMBING LEFT TURN TO 2000 DIRECT OOC NDB AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 409 AAO 314019N/0930628W CHART R-3801A. OOC NDB TO RW35: 3.43/43.					
AEX VORTAC (IAF)		SATCH INT		298.72 / 32.73				3000							
SATCH INT (IF)		OOC NDB		341.86 / 7.06				1700							
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD <u>S</u> OOC NDB, RT, 343.35 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC <u>343.35</u> FAF <u>OOC NDB</u> DIST FAF TO MAP <u>4.22</u> THLD <u>4.22</u> 4. MIN. ALT <u>OOC NDB 1700</u> 8. MSA FROM: <u>OOC NDB 2600</u>										MAG VAR: 4E		EPOCH YEAR: 1995			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-35	720	1	599	720	1	599	720	1 5/8	599		NA				
CIRCLING	720	1	599	740	1	619	740	1 3/4	619		NA				
NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT AEX VORTAC ON V212 EASTBOUND. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ALEXANDRIA INTL ALTIMETER SETTING AND (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 121		THRE: 121		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP			
NATCHITOCHES, LA		AIRPORT NAME:		NATCHITOCHES RGNL		OOC		NDB RWY 35, AMDT 6 31 MAY 2012				AMDT 5A			
												DATE 09/24/2009			

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 100 FEET AND S-35 CAT C VISIBILITY 1/8 MILE, CIRCLING CAT C VISIBILITY 1/4 MILE.

CHART NOTE: FOR INOPERATIVE ODALS INCREASE S-35 CAT C VISIBILITY 1/8 MILE.

CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-35 CAT A/B.

CITY AND STATE

NATCHITOCHES, LA

ELEVATION: 121

THRE: 121

AIRPORT NAME:

NATCHITOCHES RGNL

FACILITY
IDENTIFIER:

OOC

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

NDB RWY 35, AMDT 6

31 MAY 2012

SUP:

AMDT: 5A

DATED: 09/24/2009