

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.			
TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW05 CLIMB TO 2200 DIRECT PUKKO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 230.35 INBOUND. CHART FAS OBST: 503 ROD ON OL MCWV TWR 354836N/0904103W DISTANCE TO THLD FROM 278 HATH: 0.73 NM. CHART VDP AT 1.44 MILES TO RW05* *LNAV ONLY. WAAS CHANNEL # 77820 REFERENCE PATH ID: W05A LTP HAE: 50.2 M			
YIGUY (IF/IAF)	ZIKOP (FB)	050.11 / 7.70	2100				
ZIKOP (FAF)	WUVAX/2.10 NM TO RW05 (FB)	050.18 / 3.55					
WUVAX/2.10 NM TO RW05	RW05 (MAP) (FO)	050.18 / 2.10					
RW05 (MAP)	534 MSL	050.18					
534 MSL	PUKKO (FO)		2200				

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)			
2. HOLD SW YIGUY, RT, 050.11 INBOUND, 2300 FT. IN LIEU OF PT (IAF)			
3. FAC: <u>050.18</u> FAF: ZIKOP		DIST FAF TO MAP: <u>5.65</u> THLD: <u>5.65</u>	
4. MIN. ALT: YIGUY 2300, ZIKOP 2100, WUVAX/2.10 NM TO RW05 960*			
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u>		150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCPT: <u>2100</u> GS ALT AT: ZIKOP 2100		OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u>3.00</u> TCH: 45.0 34:1 IS NOT CLEAR			
8. MSA FROM: <u> </u>			

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	534	7/8	278	534	7/8	278	534	7/8	278	534	7/8	278			
LNAV/VNAV DA	612	1 1/8	356	612	1 1/8	356	612	1 1/8	356	612	1 1/8	356			
LNAV MDA	760	1	504	760	1	504	760	1 3/8	504	760	1 3/8	504			
CIRCLING	760	1	498	760	1	498	760	1 1/2	498	820	2	558			

NOTES:
 CHART NOTE: CIRCLING TO RWY 13-31 NA AT NIGHT.
 CHART NOTE: BARO-VNAV AND VDP NA WHEN USING WALNUT RIDGE ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -12C (11F) OR ABOVE 54C (130F).
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE	ELEVATION: 262 THRE: 256	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
JONESBORO, AR	AIRPORT NAME: JONESBORO MUNI		RNAV (GPS) RWY 5, AMDT 1	CHECKED
			7 MARCH 2013	AMDT: ORIG
				DATED 05/05/2011

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: CIRCLING NA NW OF RWY 5-23.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WALNUT RIDGE ALTIMETER SETTING AND INCREASE ALL DA 54 FEET AND ALL MDA 60 FEET. INCREASE LPV ALL CATS VISIBILITY TO 1 1/8 MILE, LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 MILE, LNAV CAT C/D AND CIRCLING CAT C VISIBILITY TO 1 5/8 MILE.

TAA

	FROM	TO	ALT
1.	320/30 CW 140/30 (NOPT)	YIGUY (IF/IAF) (FB)	2300
2.	140/30 CW 320/30	140/10 CW 320/10	3100
3.	140/10 CW 320/10	YIGUY (IF/IAF) (FO)	2300

CITY AND STATE

JONESBORO, AR

ELEVATION: 262

THRE: 256

AIRPORT NAME:

JONESBORO MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 5, AMDT 1

7 MARCH 2013

SUP:

AMDT: ORIG

DATED: 05/05/2011

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KJBR
RUNWAY	RW05
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W05A
LTP/FTP LATITUDE	354943.7155N
LTP/FTP LONGITUDE	0903904.4670W
LTP/FTP ELLIPSOIDAL HEIGHT	+00502
FPAP LATITUDE	355040.7900N
FPAP LONGITUDE	0903740.2300W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0864
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

03817E86

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00781
FPAP ORTHOMETRIC HEIGHT	+00781

QUALITY
2
CHECKED

CITY AND STATE

JONESBORO, AR

ELEVATION: 262

THRE: 256

AIRPORT NAME:

JONESBORO MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 5, AMDT 1

7 MARCH 2013

SUP:

AMDT: ORIG

DATED: 05/05/2011

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibility which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KJBRK4FR05	AYIGUY	010YIGUYK4EA0EE	AR	HF			05010040	+	02300	18000			A JS
SUSAP KJBRK4FR05	R	010YIGUYK4EA0E	I	IF				+	02300	18000			A JS
SUSAP KJBRK4FR05	R	020ZIKOPK4EA1E	F	051TF			05010077	+	02100				A JS
SUSAP KJBRK4FR05	R	020ZIKOPK4EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KJBRK4FR05	R	021WUVAXK4EA0E	S	031TF			05020036	V	0096000970		-300		A JS
SUSAP KJBRK4FR05	R	030RW05 K4PGOGY	M	031TF			05020021		00301		-300		A JS
SUSAP KJBRK4FR05	R	040	0	M	CA		0502	+	00534				A JS
SUSAP KJBRK4FR05	R	050PUKKOK4EA0EY		DF				+	02200				A JS
SUSAP KJBRK4FR05	R	060PUKKOK4EA0EE	R	HM			23040040	+	02200				A JS

[illegible][illegible]

QUALITY
2
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.


ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	YIGUY	YIGUY	010	IAF	HF	R	FO		050.1(050.1T)	004.0	AA 02300	
		YIGUY	010	FACF	IF		FB				AA 02300	
		ZIKOP	020	FAF	TF		FB	0.5	050.1(050.1T)	007.7	AA 02100	
		WUVAX	021	SDF	TF		FB	0.3	050.2(050.2T)	003.6	AA 00960 GS 00970	
		RW05	030	MAP	TF		FO	0.3	050.2(050.2T)	002.1	AT 00301	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		050.2(050.2T)		AA 00534	
	PUKKO	050		DF		FO				AA 02200	
	PUKKO	060		HM	R	FO		230.4(230.4T)	004.0	AA 02200	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	PUKKO	N355839.33	W0902551.92	N3558.656	W09025.865
	WUVAX	N354822.98	W0904103.53	N3548.383	W09041.059
	YIGUY	N354109.89	W0905140.25	N3541.165	W09051.671
	ZIKOP	N354606.46	W0904424.59	N3546.108	W09044.410
	RW05	N354943.72	W0903904.47	N3549.729	W09039.075

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW05	00256	45



CITY AND STATE JONESBORO, AR	ELEVATION: 262 THRE: 256	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 5, AMDT 1 7 MARCH 2013	SUP:
	AIRPORT NAME: JONESBORO MUNI			AMDT: ORIG
				DATED: 05/05/2011