

**Federal Aviation
Administration**

Transmittal Letter 19-17

June 28, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/15/2019	AR	Jonesboro	Jonesboro Muni	9/8783	6/18/2019	RNAV (GPS) RWY 5, Amdt 1A

AIRAC Date: 15 AUGUST 2019

FDC 9/8783 JBR IAP JONESBORO MUNI, Jonesboro, AR. RNAV (GPS) RWY 5, AMDT 1A... LPV DA 539/HAT 280.
DELETE NOTE: CIRCLING TO RWY 13-31 NA AT NIGHT. CHART NOTE: CIRCLING RWY 31 NA AT NIGHT.
DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHANGE BARO-VNAV NOTE
TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -12C OR ABOVE 54C.
CHANGE HELICOPTER NOTE TO READ: RWY 5 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT
AUTHORIZED. CHANGE WHEN LOCAL ALTIMETER SETTING NOT RECEIVED NOTE TO READ: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED, USE WALNUT RIDGE ALTIMETER SETTING: INCREASE LPV DA TO
593 FEET AND VISIBILITY 1/8 SM, AND LNAV/VNAV DA TO 669 FEET; INCREASE ALL MDAS 60 FEET AND
VISIBILITY LNAV CAT C/D 1/4 SM AND CIRCLING CAT C 1/8 SM. THIS IS RNAV (GPS) RWY 5, AMDT 1B.
1904081746-PERM