

**Federal Aviation
Administration**

Transmittal Letter 22-10

MARCH 18, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/21/2022	AR	Siloam Springs	Smith Fld	2/6587	3/7/2022	RNAV (GPS) RWY 36, Orig

AIRAC Date: 21 APRIL 2022

FDC 2/6587 SLG IAP SMITH FLD, SILOAM SPRINGS, AR. RNAV (GPS) RWY 36, ORIG... CIRCLING CAT C MDA 1800/HAA 609, CAT D MDA 1880/HAA 689. CIRCLING VISIBILITY CAT C 1 3/4, CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE NORTHWEST ARKANSAS NTL ALTIMETER SETTING AND INCREASE LPV DA TO 1469 FEET, INCREASE LNAV/VNAV DA TO 1587 FEET; INCREASE ALL MDAS 40 FEET. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 36, ORIG-A. 2202221535-PERM