

**Federal Aviation  
Administration**

**Transmittal Letter 21-23**

**September 17, 2021**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: .....EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/4/2021	AL	Eufaula	Weedon Fld	1/2815	7/26/2021	VOR RWY 18, Amdt 8A

**AIRAC Date: 4 NOVEMBER 2021**

FDC 1/2815 EUF IAP WEEDON FLD, EUFAULA, AL. VOR RWY 18, AMDT 8A... CIRCLING CAT C/D MDA 1060/HAA 775. AFENY FIX MINIMUMS: CIRCLING CAT C/D MDA 1060/HAA 775, VIS CAT C 2 1/4. CHANGE NOTE TO READ: USE CLAYTON ALTIMETER SETTING; WHEN NOT RECEIVED, USE COLUMBUS, GA ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET AND CIRCLING CAT C AND D VISIBILITY 1/4 SM; AFENY FIX MINIMUMS: INCREASE CIRCLING CAT C AND D VISIBILITY 1/4 SM. THIS IS VOR RWY 18, AMDT 8B. 2106142012-PERM