

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
 LOC STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 6.78 MILES AFTER ALMND LOM/7.94 DME OR AT I-BVX 1.16 DME FIX
ARG VORTAC	ALMND LOM/ 7.94 DME	235.61 / 47.82	3000	CLIMB TO 1200 THEN CLIMBING RIGHT TURN TO 3000 DIRECT ALMND LOM/7.94 DME AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD W, RT, 078.80 INBOUND. CHART FAS OBST: 619 TREE 354313N/0914301W CHART 1464 TOWER 354157N/0914727W. CHART VDP AT 2.36 DME; DISTANCE VDP TO THLD 1.20 MILES. ALMND LOM TO RW8: 3.06/45.

- PT L SIDE OF COURSE 258.80 OUTBOUND 3000 FT WITHIN 10 MILES OF ALMND LOM (IAF)
-
- FAC 078.80 FAF ALMND LOM/ 7.94 DME DIST FAF TO MAP 6.78 THLD 6.78
- MIN. ALT ALMND LOM 2700, CUCAL/ 4.56 DME 1560*
- MSA FROM: BV LOM 360-180 2600, 180-360 3600

MAG VAR: 1E

EPOCH YEAR:2005

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY ==>>>>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-8	1560	1 1/4	1097	1560	1 1/2	1097	1560	3	1097	1560	3	1097			
CIRCLING	1560	1 1/4	1095	1560	1 1/2	1095	1560	3	1095	1560	3	1095			
CUCAL FIX MINIMUMS															
S-8	880	1	417	880	1	417	880	1 1/4	417	880	1 1/4	417			
CIRCLING	980	1	515	980	1	515	980	1 1/2	515	1040	2	575			

NOTES:

CHART NOTE: CIRCLING TO RWY 18-36 NA AT NIGHT.
 CHART NOTE: CIRCLING NA NW OF RWY 8 AND 26.
 CHART NOTE: ADF REQUIRED.
 CHART PLANVIEW NOTE: ADF REQUIRED.
 (SEE FORM 8260-10)



CITY AND STATE BATESVILLE, AR	ELEVATION: 465 TDZE: 463 AIRPORT NAME: BATESVILLE RGNL	FACILITY IDENTIFIER: I-BVX	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LOC RWY 8, AMDT 1 18 NOV 2010	SUP	LOC RWY 7
				AMDT	ORIG
				DATE	09/01/2005

LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VDP NA WITH SEARCY ALTIMETER SETTING.

*1600 WHEN USING SEARCY ALTIMETER SETTING.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SEARCY ALTIMETER SETTING AND INCREASE

ALL MDA 100 FEET. INCREASE CUCAL FIX MINIMUMS 5-8 CAT C VISIBILITY 1/4 MILE, CAT D 1/2 MILE AND

CIRCLING CAT C/D VISIBILITY 1/4 MILE.

CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY

CITY AND STATE

BATESVILLE, AR

ELEVATION: 465

TDZE: 463

AIRPORT NAME

BATESVILLE RGNL

FACILITY
IDENTIFIER:

1-BVX

PROCEDURE NO / AMDT NO / EFFECTIVE DATE:

LOC RWY 8, AMDT 1

SUP: LOC RWY 7

AMDT: ORIG

DATED: 09/01/2005