

QUALITY
CHECKED

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 40 FT AND S-2 VISIBILITY CATS C/D 1/4 MILE.

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-2 VISIBILITY CATS C/D TO 1 1/2 MILE, USING SACRAMENTO INTL ALTIMETER SETTING, INCREASE S-2 VISIBILITY CATS C/D TO 1 3/4 MILE,



CITY AND STATE SACRAMENTO, CA	ELEVATION: 24	TDZE: 21	FACILITY IDENTIFIER: SAC	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 2, AMDT 10A 6 FEBRUARY 2014	SUP:
	AIRPORT NAME:				AMDT: 10
	SACRAMENTO EXECUTIVE				DATED: 11/20/2008