

U.S. Department of Transportation Federal Aviation Administration		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES					MISSED APPROACH										
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: MAHYE CLIMBING LEFT TURN TO 3600 DIRECT BECNA AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1578 TOWER 373809N/0971212W FAC CROSSES MID POINT OF RWY 17-35 CHART MCCONNELL AFB CHART BEECH FACTORY CHART A-683 ROUTE TYPE: A, P ROUTE TYPE QUALIFIER: 2: C											
HEGER (IAF)(40E)(43A)	BECNA (NoPT)(TF)(FB)(40E)(41E)	009.89/5.00	3600												
SOCOL (IAF)(40E)(43A)	BECNA (NoPT)(TF)(FB)(40E)(41E)	189.93/5.00	3600												
BECNA (IF/IAF)(40E)(43I)	FOGOR (TF)(FB)(40E)(43F)	279.91/6.12	3000												
FOGOR (FAF)(40E)(43F)	MAHYE (TF)(FO)(40E)(41Y)(43M)	279.82/4.77													
MAHYE (MAP)(40E)(41Y)(43M)	1778 MSL (CA)(42M)	279.82													
1778 MSL	BECNA (DF)(FO)(40E)(41E)(43H)		3600												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD E BECNA, RT, 279.91 INBOUND, 3600 FT IN LIEU OF PT (IAF)(HF)(40E)(43C) 3. FAC: <u>279.82</u> FAF: <u>FOGOR</u> DIST FAF TO MAP: <u>4.77</u> THLD: _____ 4. MIN. ALT: BECNA 3600, FOGOR 3000 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS CLEAR 8. MSA FROM: _____				MAG VAR: 8E EPOCH YEAR: 1980											
MINIMUMS															
TAKEOFF:	<input checked="" type="checkbox"/> STANDARD	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A	<input checked="" type="checkbox"/>										
CATEGORY =====>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
CIRCLING	1920	1	542	1920	1	542	1920	1 1/2	542		NA				
NOTES: CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. USE WICHITA MID-CONTINENT ALTIMETER SETTING; WHEN NOT RECEIVED, USE COLONEL JAMES JABARA ALTIMETER SETTING.															
CITY AND STATE		ELEVATION: 1378 TDZE:		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:					
WICHITA, KS		AIRPORT NAME: CESSNA ACFT FIELD		RNAV		OCT 25 2007 RNAV (GPS)-D, AMDT 1				AMDT: ORIG-A					
										DATE 11/25/2004					



**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	190/30 CW 010/30 (NOPT)	BECNA (IF/IAF) (FB)	3600
2.	010/30 CW 100/30	HEGER (IAF) (FB)	3600
3.	100/30 CW 190/30	SOCOL (IAF) (FB)	3600

CITY AND STATE

WICHITA, KS

ELEVATION: 1378 TDZE:

AIRPORT NAME:

CESSNA ACFT FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS)-D, AMDT 1

OCT 25 2007

SUP:

AMDT: ORIG-A

DATED: 11/25/2004

