

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES											MISSED APPROACH								
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW21 CLIMB TO 2800 DIRECT FAYYE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 030.55 INBOUND. CHART FAS OBST: 1259 TREE 443521N/0892928W 1430 AAO 443713N/0892802W DISTANCE TO THLD FROM 250 HAT: 0.65 NM. CHART VDP AT 1.17 NM TO RW21* *LNAV ONLY. WAAS CHANNEL # 86511 REFERENCE PATH ID: W21A LTP HAE: 302.5 M									
CLIDE (IAF)		JUVOP (NOPT) (TF) (FB) (RNP 1.00)			120.64 / 6.40			2900											
ACEBE (IAF)		JUVOP (NOPT) (TF) (FB) (RNP 1.00)			300.82 / 6.40			2900											
JUVOP (IF/IAF)		ODUYA (TF) (FB) (RNP 1.00)			210.73 / 6.22			2800											
ODUYA (FAF)		RW21 (MAP) (TF) (FO) (RNP 0.30)			210.68 / 5.17														
RW21 (MAP)		1360 MSL (CA)			210.68			2800											
1360 MSL		FAYYE (DF) (FO) (RNP 1.00)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE JUVOP, RT, 210.73 INBOUND, 2900 FT. IN LIEU OF PT (IAF) 3. FAC: 210.68 FAF: ODUYA DIST FAF TO MAP: 5.17 THLD: 5.17 4. MIN. ALT: JUVOP 2900, ODUYA 2800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2800 GS ALT AT: ODUYA 2800 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 43.9 34:1 IS CLEAR 8. MSA FROM: _____																MAG VAR: 1W		EPOCH YEAR: 1995	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	1360	3/4	250	1360	3/4	250	1360	3/4	250	1360	3/4	250							
LNAV/VNAV DA	1457	7/8	347	1457	7/8	347	1457	7/8	347	1457	7/8	347							
LNAV MDA	1520	3/4	410	1520	3/4	410	1520	1	410	1520	1	410							
CIRCLING	1580	1	470	1600	1	490	1820	2	710	1820	2 1/4	710							
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F). @ CAT D 800-2 1/4 CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV CAT C AND D VISIBILITY TO 1 1/8 SM.																			
CITY AND STATE		ELEVATION: 1110 TDZE: 1110			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:							
STEVENS POINT, WI		AIRPORT NAME:			STEVENS POINT MUNI		RNAV (GPS) RWY 21, AMDT 1					AMDT: ORIG							
							22 JUNE 2017					DATED 03/12/2009							



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	121/30 CW 301/30 (NOPT)	121/10 CW 301/10	3600
	121/10 CW 301/10	JUVOP (IF/IAF) (FB)	2900
2.	301/30 CW 031/30	ACEBE (IAF) (FB)	2900
3.	031/30 CW 121/30	CLIDE (IAF) (FB)	3100



CITY AND STATE

STEVENS POINT, WI

ELEVATION: 1110

TDZE: 1110

AIRPORT NAME:

STEVENS POINT MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 21, AMDT 1

22 JUNE 2017

SUP:

AMDT: ORIG

DATED: 03/12/2009

**STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSTE
RUNWAY	RW21
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W21A
LTP/FTP LATITUDE	443310.0800N
LTP/FTP LONGITUDE	0893130.6100W
LTP/FTP ELLIPSOIDAL HEIGHT	+03025
FPAP LATITUDE	443152.6360N
FPAP LONGITUDE	0893232.2095W
THRESHOLD CROSSING HEIGHT (TCH)	00043.9
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0912
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

339CBF2B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+03383
FPAP ORTHOMETRIC HEIGHT	+03383

QUALITY
4
CHECKED

CITY AND STATE STEVENS POINT, WI	ELEVATION: 1110 TDZE: 1110 AIRPORT NAME: STEVENS POINT MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, AMDT 1 22 JUNE 2017	SUP:
				AMDT: ORIG
				DATED: 03/12/2009