

**Federal Aviation
Administration**

Transmittal Letter 21-08

February 19, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
3/25/2021	NC	Wadesboro	Anson County - Jeff Cloud Fld	1/9914	2/5/2021	RNAV (GPS) RWY 34, Amdt 2A

25 MARCH 2021

FDC 1/9914 AFP IAP ANSON COUNTY - JEFF CLOUD FLD, WADESBORO, NC. RNAV (GPS) RWY 34, AMDT 2A... LPV ALL CAT VIS 3/4. LNAV/VNAV DA 957/HAT 658, ALL CATS VIS 1 7/8. CIRCLING CAT C MDA 1080/HAA 780, CAT C VIS 2 1/4, CAT D MDA 1080/HAA 780, CAT D VIS 2 1/2. DELETE NOTE: WHEN VGSI INOP, CIRCLING RWY 16 NA AT NIGHT. CHART NOTE: CIRCLING RWY 16 NA AT NIGHT. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 42C (107F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 42C. DELETE NOTE: DME/DME RNP-0.3 NA. CHART PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROCKINGHAM ALTIMETER SETTING: INCREASE LPV DA TO 598 AND LPV ALL CATS VISIBILITY 1/8 MILE; INCREASE LNAV/VNAV DA TO 1005 AND LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE; INCREASE ALL MDA 60 FEET AND LNAV CATS C/D AND CIRCLING CAT C VISIBILITY 1/8 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROCKINGHAM ALTIMETER SETTING: INCREASE LPV DA TO 598 AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1006 AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDA 60 FEET, LNAV VISIBILITY CATS C/D 1/8 SM AND CIRCLING VISIBILITY CAT D 1/4 SM. ALTERNATE MINIMUMS STANDARD EXCEPT CAT C 800-2 1/4, CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 34, AMDT 2B. 2102021539-PERM