

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

| | | | | | | |
|---------------------------------|--|--|---|----------------------------|-----------------------|---------------------------|
| <u>AIRPORT ID</u> 0S9 | <u>PROCEDURE NAME</u> RNAV (GPS) -A | <u>ORIGINAL/AMENDMENT</u> 1 | <u>CITY</u> PORT TOWNSEND | <u>STATE</u> WA | | |
| <u>AIRPORT ELEVATION</u> 110 | <u>TDZE</u> | <u>SUPERSEDED</u> RNAV (GPS)-A | <u>ORIGINAL/AMENDMENT</u> ORIG-B | <u>DATED</u> 04/21/2022 | <u>MAG VAR</u> 16E | <u>EPOCH YEAR</u> 2015 |
| <u>FACILITY</u> RNAV | <u>COORDINATES OF FACILITIES</u> | <u>ACTUAL EFFECTIVE DATE</u> 15 JUNE 2023 | <u>REQUIRED EFFECTIVE DATE</u> ROUTINE | <u>CANCEL/SUSPEND</u> | | |

TERMINAL ROUTES

| <u>FROM</u> | <u>FIX TYPE</u> | <u>TO</u> | <u>FIX TYPE</u> | <u>LEG TYPE</u> | <u>FO/FB</u> | <u>RNP</u> | <u>COURSE</u> | <u>DISTANCE</u> | <u>ALTITUDE</u> |
|--------------------|------------------------|------------------|------------------------|------------------------|---------------------|-------------------|----------------------|------------------------|------------------------|
| JAWBN | | YAYUB | | TF | FO | 1.00 | 275.80 | 11.24 | 4300 |
| WATTR | | YAYUB | | TF | FO | 1.00 | 234.56 | 6.89 | 3200 |
| JIGEB | | YAYUB | | TF | FO | 1.00 | 185.58 | 8.44 | 3200 |
| YAYUB | IF/IAF | WIKUV | | TF | FB | 1.00 | 087.44 | 7.70 | 2000 |
| WIKUV | FAF | RW09 | MAP | TF | FO | 0.30 | 087.58 | 4.14 | |
| RW09 | MAP | 510 MSL | | CA | | | 087.58 | | |
| 510 MSL | | WATTR | | DF | FO | 1.00 | | | 5400 |

MISSED APPROACH

MAP:
RW09

MISSED APPROACH INSTRUCTIONS:

CLIMBING LEFT TURN TO 5400 DIRECT WATTR AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5400.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF

(IAF)

2. HOLD W YAYUB, LT, 087.44 INBOUND, 3200 FT. IN LIEU OF PT (IAF), MAX 6000.

3. FAC: 087.58FAF: WIKUVDIST FAF TO MAP: 4.14DIST FAF TO THLD:

4. MIN ALT: YAYUB 3200, WIKUV 2000

5. DIST TO THLD FROM OM:MM:IM:150 HAT:GS ANT:

6. MIN GP INCPT:GP ALT AT FAF :OM:MM:IM:

7. GP ANGLE:34:1: IS NOT CLEAR20:1: IS NOT CLEARTCH:

8. MSA FROM: ARP OS9 9000

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.
CHART NOTE: RWY 9, 27 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WATTR ON T268 EASTBOUND.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT JAWBN ON V4 EASTBOUND.

ADDITIONAL FLIGHT DATA:

CHART CHINOOK B MOA
WIKUV TO RW09 4.20/43
HOLD NW, RT, 133.08 INBOUND.
FAS OBST: 700 AAO 480414N/1225119W.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA☐CAT A, B 900-2.; NA WHEN LOCAL WEATHER NOT AVAILABLE

| CATEGORY: | A | | | B | | | C | | | D | | | E | | |
|------------|--------|-------|---------|--------|-------|---------|--------|-----|---------|--------|-----|---------|--------|-----|---------|
| FINAL TYPE | DA/MDA | VIS | HAT/HAA | DA/MDA | VIS | HAT/HAA | DA/MDA | VIS | HAT/HAA | DA/MDA | VIS | HAT/HAA | DA/MDA | VIS | HAT/HAA |
| CIRCLING | 960 | 1 1/4 | 850 | 980 | 1 1/4 | 870 | | NA | | | NA | | | | |



