

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD SW DROOL, LT, 064.30 INBOUND, 2700 FT. IN LIEU OF PT (IAF)				
3. FAC	064.30	FAF DROOL INT/LFD 21.00 DME	DIST FAF TO MAP		5.43 THLD 5.43
4. MIN. ALT	DROOL 2700				
8. MSA FROM:	LFD VOR/DME 045-315 2600, 315-045 3000				

MAG VAR: 5W

EPOCH YEAR: 1995

[illegible]

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.  
CHART NOTE: CIRCLING TO RWY 16-34 NA.  
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STURGIS ALTIMETER SETTING AND INCREASE ALL MDAS 60FT AND S-7 CAT C VISIBILITY 1/4 MILE.

CITY AND STATE COLDWATER, MI	ELEVATION: 959	TDZE: 959	FACILITY IDENTIFIER: LFD	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 7, AMDT 5  APR 10 2008	SUP	
	AIRPORT NAME:				AMDT	4B
	BRANCH COUNTY MEMORIAL				DATE	05/14/2001