

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
ILS STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KEEN	<u>PROCEDURE NAME</u> ILS OR LOC RWY 2	<u>ORIGINAL/AMENDMENT</u> 6	<u>CITY</u> KEENE	<u>STATE</u> NH		
<u>AIRPORT ELEVATION</u> 488	<u>TDZE</u> 488	<u>SUPERSEDED</u> ILS OR LOC RWY 2	<u>ORIGINAL/AMENDMENT</u> 5	<u>DATED</u> 10/07/2021	<u>MAG VAR</u> 15W	<u>EPOCH YEAR</u> 1995
<u>FACILITY</u> I-EEN	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 24 MARCH 2022	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
GDM VOR/DME	IAF	CAHOW INT/EEN DME 6.71 DME	NOPT				323.08	13.02	3100
CAHOW INT/EEN DME 6.71 DME	IF/IAF	JURGI INT					018.24	5.80 (I-EEN)	2600

MISSED APPROACH

MAP:

ILS: DA
LOC: 6.50 NM AFTER JURGI INT OR AT EEN DME 5.66 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1540 THEN CLIMBING LEFT TURN TO 3100 ON HEADING 200 AND GDM VOR/DME R-323 TO CAHOW INT/GDM VOR/DME 13.02 DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S CAHOW, LT, 018.24 INBOUND, 3100 FT. IN LIEU OF PT (IF/IAF), MAX 4900.
- FAC: 018.24 FAF: JURGI INT DIST FAF TO MAP: 6.50 DIST FAF TO THLD: 6.50
- MIN ALT: CAHOW INT/EEN DME 6.71 DME 3100, JURGI INT 2600, CIMVI/EEN DME 1.63 DME 1840
- DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: 960
- MIN GS INCPT: 2600 GS ALT AT PFAF: JURGI INT 2600 OM: MM: IM:
- GP ANGLE: 3.00 34:1: 20:1: TCH: 42.6
- MSA FROM: GDM VOR/DME 060-330 3300, 330-060 4400

EQUIPMENT REQUIREMENTS NOTES:

DME REQUIRED FOR LOC ONLY.

QUALITY
33
CHECKED

