

**Federal Aviation  
Administration**

**Transmittal Letter 21-05**

**JANUARY 8, 2021**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
2/25/2021	MN	Marshall	Southwest Minnesota Rgnl	0/2066	11/24/2020	RNAV (GPS) RWY 12, Amdt 1A

**25 FEBRUARY 2021**

FDC 0/2066 MML IAP SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD, MARSHALL, MN. RNAV (GPS) RWY 12, AMDT 1A... DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CARIT ON V26 WESTBOUND. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTES: RNP APCH. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 36C (96F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 36C. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TRACY MUNI ALTIMETER SETTING AND INCREASE ALL DA 58 FEET AND ALL MDA 60 FEET. INCREASE LNAV/VNAV AND LNAV CATS C/D VISIBILITY TO 3/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TRACY MUNI ALTIMETER SETTING AND INCREASE LPV DA TO 1441, LNAV/VNAV DA TO 1548, AND LNAV/VNAV ALL CATS VISIBILITY 1/8 SM; INCREASE ALL MDAS 60 FEET AND LNAV CAT C/D VISIBILITY 1/8 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV CATS C/D VISIBILITY TO 1 MILE. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 7/8 SM, AND LNAV CAT C/D VISIBILITY TO 1 SM. DELETE NOTE: FOR INOPERATIVE MALSR WHEN USING TRACY MUNI ALTIMETER SETTING, INCREASE LPV ALL CATS TO 7/8 MILE. CHART NOTE: FOR INOPERATIVE ALS WHEN USING TRACY MUNI ALTIMETER SETTING, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 SM.. THIS IS RNAV (GPS) RWY 12, AMDT 1B. 2005191404-PERM