

**Federal Aviation
Administration**

Transmittal Letter 21-15

MAY 28, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/15/2021	MN	Marshall	Southwest Minnesota Rgnl	1/9869	5/12/2021	RNAV (GPS) RWY 12, Amdt 1B

Airac Date: 15 JULY 2021

FDC 1/9869 MML IAP SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD, MARSHALL, MN. RNAV (GPS) RWY 12, AMDT 1B... CIRCLING CAT C MDA 1820/HAA 637, CAT D MDA 1840/HAA 657, CAT C VIS 1 3/4. DELETE PBN REQUIREMENTS NOTE: RNP APCH. CHART PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TRACY MUNI ALTIMETER SETTING AND INCREASE LPV DA TO 1441 FEET; LNAV/VNAV DA TO 1548 AND ALL CATS VISIBILITIES 1/8 SM; INCREASE ALL MDA 60 FEET, LNAV VISIBILITY CAT C/D 1/8 SM AND CIRCLING VISIBILITY CAT C/D 1/4 SM. THIS IS RNAV (GPS) RWY 12, AMDT 1C.
2105041243-PERM