

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
HASSL	ONE	HASSL1.HASSL	NONE		25JAN2024
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 13: CLIMB ON HEADING 125.18 TO 6237, THEN DIRECT UVCEH, THEN ON TRACK 078.14 TO HASSL.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:**PBN REQUIREMENTS NOTES:**

RNAV 1 - GPS.

EQUIPMENT REQUIREMENT NOTES:**TAKEOFF MINIMUMS:**

RWY 31: NA - TERRAIN.

RWY 13: STANDARD.

TAKEOFF OBSTACLES NOTES:

RWY 13: LIGHT POLES 10 FT FROM DER, 19 FT LEFT OF CENTERLINE, 4 FT AGL/5721 FT MSL.

TREE 32 FT FROM DER, 353 FT LEFT OF CENTERLINE, 5730 FT MSL.

TREES BEGINNING 67 FT FROM DER, 198 FT LEFT OF CENTERLINE, UP TO 15 FT AGL/5734 FT MSL.

TREES BEGINNING 381 FT FROM DER, 473 FT LEFT OF CENTERLINE, UP TO 5735 FT MSL.

TREES BEGINNING 703 FT FROM DER, 277 FT LEFT OF CENTERLINE, UP TO 5744 FT MSL.

TREE 798 FT FROM DER, 481 FT LEFT OF CENTERLINE, 5747 FT MSL.

TREES BEGINNING 811 FT FROM DER, 336 FT LEFT OF CENTERLINE, UP TO 5752 FT MSL.

TREES BEGINNING 881 FT FROM DER, 441 FT LEFT OF CENTERLINE, UP TO 5756 FT MSL.

TREES BEGINNING 996 FT FROM DER, 361 FT LEFT OF CENTERLINE, UP TO 5765 FT MSL.

TREE, TERRAIN BEGINNING 1119 FT FROM DER, 509 FT LEFT OF CENTERLINE, UP TO 5772 FT MSL.

TREE, VEHICLES ON ROAD BEGINNING 1228 FT FROM DER, 160 FT LEFT OF CENTERLINE, UP TO 5774 FT MSL.

TREES BEGINNING 1332 FT FROM DER, 402 FT LEFT OF CENTERLINE, UP TO 5775 FT MSL.

TRANSMISSION LINES, TREES, VEHICLE ON ROAD BEGINNING 1439 FT FROM DER, 208 FT LEFT OF CENTERLINE, UP TO 5786 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLE MANDATING ROUTE DEVELOPMENT: RWY 13: 10836 FT MSL AAO 374524.00N/1115227.00W.

MSA:
MSA FROM 1L7 12600

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:
DME/DME ASSESSMENT: NOT CONDUCTED.
MV: 1L7 14E/1985.

AIRPORTS SERVED:		
AIRPORT ID	CITY	STATE
1L7	ESCALANTE	UT

COMMUNICATIONS:

FIXES AND/OR NAVAIDS:

REMARKS:
APPLIED 50' VEGETATION PER FPT.

<u>FLIGHT INSPECTED BY</u>		<u>OFFICE</u>	<u>DATE</u>	
BRANDON C EASTIN	Digitally signed by ROBERT G HAMILTON	FPO	05/25/2023	
	Nov 28, 2023			
<u>DEVELOPED BY</u>		<u>OFFICE</u>	<u>DATE</u>	
FRANK MOORE	FRANCIS HUDSON MOORE	AJV-A433	01/30/2023	
	 Digitally signed by FRANCIS HUDSON MOORE Date: 2023.02.17 13:18:15 -05'00'			
<u>APPROVED BY</u>		<u>OFFICE</u>	<u>DATE</u>	<u>TITLE</u>
JOHNNIE BAKER	Digitally signed by CASIMIR L TABAKA	AJV-A430		MANAGER
	Feb 23, 2023			

REQUIRED EFFECTIVE DATE
ROUTINE

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZLC, ARPT MGR

CHANGES - REASONS:
ORIGINAL



NFDD No. 233				12/06/2023				48			
FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE DEPARTURE (DATA RECORD)											
DP NAME						NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE	
HASSL						ONE	HASSL1.HASSL	NONE		25JAN2024	
FIX/NAVAID		LAT/LONG		C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW13 (AER)		374502.11N/1113433.12		N	-	-	-	-			
6237 MSL		--		-		VA	139.18	-	AT/ABOVE 6237		
UVCEH		373511.13N/1112351.65W		Y	FB	DF	-	-			
HASSL		373412.08N/1105300.63W		Y	FB	TF	092.14	24.54			

