

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: RHI VOR/DME								
RHI VOR/DME			INILE/RHI 5.00 DME			101.00 / 5.00			3900		CLIMB TO 3900 THEN LEFT TURN DIRECT RHI VOR/DME AND HOLD.								
PEWLE/RHI 10.00 DME CW (IAF)			DAPAC/RHI 10.00 DME (NOPT)			10.00 DME ARC			4300										
PEPVY/RHI 10.00 DME CCW (IAF)			DAPAC/RHI 10.00 DME (NOPT)			10.00 DME ARC			4300										
DAPAC/RHI 10.00 DME (IF)			JIMOB/RHI 8.00 DME			281.00 / 2.00			3900										
JIMOB/RHI 8.00 DME			INILE/RHI 5.00 DME			281.00 / 3.00			3300		ADDITIONAL FLIGHT DATA: HOLD W, RT, 101.00 INBOUND. CHART FAS OBST: 1963 TOWER 453807N/0892243W CHART RHI R-301 AT PEWLE. CHART RHI R-156 AT PEPVY. INILE TO RW27: 3.08/50. FAC CROSSES RWY C/L EXTENDED 4587 FT FROM THLD.								
1. PT <u>R</u> SIDE OF COURSE <u>101.00</u> OUTBOUND <u>3900</u> FT WITHIN <u>10</u> MILES OF <u>INILE</u> (IAF)																			
2.																			
3. FAC <u>281.00</u> FAF <u>INILE/RHI 5.00 DME</u> DIST FAF TO MAP <u>          </u> THLD <u>5.05</u>																			
4. MIN. ALT <u>JIMOB 3900, INILE 3300</u>																			
8. MSA FROM: <u>RHI VOR/DME 360-180 4400, 180-360 3300</u>										MAG VAR: <u>2E</u> EPOCH YEAR: <u>1965</u>									
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: <u>N A</u>		STANDARD							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-27		2220	1	614	2220	1	614	2220	1 3/4	614	2220	1 3/4	614						
CIRCLING		2220	1	596	2220	1	596	2260	1 3/4	636	2280	2	656						
NOTES:  CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TOMAHAWK ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND CAT C/D VISIBILITY 1/4 MILE.																			
CITY AND STATE RHINELANDER, WI		ELEVATION: 1624 TDZE: 1606 AIRPORT NAME:  RHINELANDER-ONEIDA COUNTY			FACILITY IDENTIFIER: RHI			PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 27, ORIG-H 2 MARCH 2017				SUP 4 AMDT DATE 08/18/2016			QUALITY 4 ORIG CHECKED				