

U.S. Department
of Transportation

800 Independence Ave., S.W.
Washington D.C. 20591

**Federal Aviation
Administration**

Transmittal Letter 20-09

March 6, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as
follows:

.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	MI	Iron Mountain Kingsford	Ford	0/9688	2/26/2020	RNAV (GPS) RWY 1, Orig-A

AIRAC Date: 23 APRIL 2020

FDC 0/9688 IMT IAP FORD, IRON MOUNTAIN KINGSFORD, MI. RNAV (GPS) RWY 1, ORIG-A... CHART CIRCLING
ICON. CIRCLING CAT B MDA 1780/HAA 598, CAT D MDA 1840/HAA 658. CHART NOTE: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE ESCANABA ALTIMETER SETTING AND INCREASE ALL DA/MDA 180 FEET, INCREASE
LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS VISIBILITY 3/4 SM, LNAV CAT C/D VISIBILITY 1/2 SM, AND
CIRCLING CAT B VISIBILITY 1/4 SM, CAT C/D VISIBILITY 3/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING
NOT RECEIVED, USE ESCANABA ALTIMETER SETTING AND INCREASE ALL DA/MDA 180 FEET, INCREASE LPV ALL
CATS VISIBILITY 1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 3/4 MILE, LNAV CAT C AND D VISIBILITY 1/2 MILE,
AND CIRCLING CAT B VISIBILITY 1/4 MILE, CAT C AND D VISIBILITY 1/2 MILE.. THIS IS RNAV (GPS) RWY 1, ORIG-B.
2002261610-PERM