

**Federal Aviation
Administration**

Transmittal Letter 22-21

August 19, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/6/2022	TN	Athens	McMinn County	2/3856	8/5/2022	RNAV (GPS) RWY 20, Amdt 1C

AIRAC Date: 6 OCTOBER 2022

FDC 2/3856 MMI IAP MCMINN COUNTY, ATHENS, TN. RNAV (GPS) RWY 20, AMDT 1C...
PBN REQUIREMENTS NOTE: RNP APCH -GPS. DELETE NOTE: DME/DME RNP-0.3 NA.
DELETE NOTE: *LNAV ONLY. DELETE NOTE: NIGHT LANDING: RWY 2 NA. CHART NOTE:
CIRCLING RWY 2 NA AT NIGHT. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-
VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. CHANGE NOTE TO READ:
RWY 20 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE
NOTE: BARO-VNAV NA WHEN USING MC GHEE TYSON ALTIMETER SETTING. DELETE
NOTE VDP NA WHEN USING MC GHEE TYSON ALTIMETER SETTING. CHART NOTE:
BARO-VNAV AND VDP NA WHEN USING MC GHEE TYSON ALTIMETER SETTING. CHANGE
NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MC GHEE
TYSON ALTIMETER SETTING: INCREASE LPV DA TO 1279 FEET AND ALL CATS VISIBILITY
1/8 SM; LNAV/VNAV DA TO 1823 FEET AND ALL CATS VISIBILITY 1 1/2 SM; INCREASE ALL
MDAS 120 FEET AND LNAV VISIBILITY CATS C/D 1/2 SM, AND CIRCLING CATS A/C
VISIBILITY 1/4 SM. LNAV/VNAV VISIBILITY ALL CATS 2 1/2 SM. LNAV VISIBILITY CATS C/D
2 SM. DELETE PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI
ANGLE 3.00/TCH 50). THIS IS RNAV (GPS) RWY 20, AMDT 1D. 2205131057-PERM