

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW18 CLIMB TO 3000 DIRECT HISTU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, LT, 356.28 INBOUND. CHART FAS OBST: 983 TOWER 400619N/0933623W DISTANCE TO THLD FROM 297 HATH: 0.81 NM. WAAS CHANNEL # 99626 REFERENCE PATH ID: W18A LTP HAE: 198.5 M	
JAWED	HEMGA (FB)	044.72 / 20.26	3000		
YIGRE	SIXFY (FB)	333.15 / 11.86	3000		
HEMGA (IAF)	BILLE (NOPT) (FB)	086.19 / 5.00	3000		
SIXFY (IAF)	BILLE (NOPT) (FB)	266.33 / 5.00	3000		
BILLE (IF/IAF)	IMKAW (FB)	176.26 / 5.02	2500		
IMKAW (FAF)	JABOP/2.50 NM TO RW18 (FB)	176.26 / 2.85			
(SEE FORM 8260-10)					
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD N BILLE, RT, 176.26 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>176.26</u> FAF: <u>IMKAW</u> DIST FAF TO MAP: <u>5.35</u> THLD: <u>5.35</u> 4. MIN. ALT: <u>BILLE 3000, IMKAW 2500, JABOP/2.50 NM TO RW18 1580*</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>2500</u> GS ALT AT: <u>IMKAW 2500</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS NOT CLEAR 8. MSA FROM: <u>RW18 2600</u>					
				MAG VAR: 3E EPOCH YEAR: 2000	
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A X		
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LPV DA	1054	1	297	1054	1
LNAV/VNAV DA	1248	1 3/4	491	1248	1 3/4
LNAV MDA	1180	1	423	1180	1
CIRCLING	1340	1	582	1340	1
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: USE CHILLICOTHE ALTIMETER SETTING. WHEN NOT RECEIVED, USE KIRKSVILLE ALTIMETER SETTING AND INCREASE ALL DA 93 FEET AND ALL MDA 100 FEET. INCREASE LPV VISIBILITY 3/8 MILE ALL CATS AND LNAV/VNAV 1/4 ALL CATS. CHART NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)					
CITY AND STATE		ELEVATION: 758 THRE: 757		FACILITY IDENTIFIER: RNAV	
TRENTON, MO		AIRPORT NAME: TRENTON MUNI		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 26 JULY 2012	
				SUP: AMDT: NONE DATED	

QUALITY
1
CHECKED

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
JABOP/2.50 NM TO RW18	RW18 (MAP) (FO)	176.26 / 2.50	
RW18 (MAP)	1054 MSL	176.26	
1054 MSL	HISTU (FO)		3000

NOTES, (CONT.):

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT JAWED ON V13-161 SOUTHBOUND.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

*LNAV ONLY

QUALITY
1
CHECKED

CITY AND STATE

TRENTON, MO

ELEVATION: 758

THRE: 757

AIRPORT NAME:

TRENTON MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG
26 JULY 2012

SUP:

AMDT: NONE

DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KTRX
RUNWAY RW18
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W18A
LTP/FTP LATITUDE 400518.0315N
LTP/FTP LONGITUDE 0933526.5940W
LTP/FTP ELLIPSOIDAL HEIGHT +01985
FPAP LATITUDE 400348.8700N
FPAP LONGITUDE 0933525.0900W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1560
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

DA76EA0B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K3
LTP ORTHOMETRIC HEIGHT +02307
FPAP ORTHOMETRIC HEIGHT +02307

QUALITY
2
CHECKED

CITY AND STATE

TRENTON, MO

ELEVATION: 758

THRE: 757

AIRPORT NAME:

TRENTON MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG

26 JULY 2012

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
1
CHECKED

CITY AND STATE TRENTON, MO	ELEVATION: 758 THRE: 757 AIRPORT NAME: TRENTON MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 26 JULY 2012	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
RUNWAY	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

SUSAP KTRXK3GRW18	0043071763	N40051803W093352659-0100											

PP	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

SUSAP KTRXK3PR18	RW18 001	0000W18A0N4005180315W09335265940+019850300N4003488700W09335250900106751560000400F400500DA76EA0B											
SUSAP KTRXK3PR18	RW18 002E	+02307+02307LPV	99626										

MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

SUSAP KTRXK3SRW18	K3PG	0	18018002625										M

QUALITY
CHECKEDCITY AND STATE
TRENTON, MOELEVATION: 758 THRE: 757
AIRPORT NAME:
TRENTON MUNIFACILITY
IDENTIFIER:
RNAVPROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 18, ORIG
26 JULY 2012SUP:
AMDT: NONE
DATED: