

## U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

## VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## TERMINAL ROUTES

## MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
BVO VOR/DME	SCATT/8.50 DME	167.71 / 8.50	2500
TUL VORTAC (IAF)	AVANT/15.00 DME	328.75 / 25.34	2500
AVANT/15.00 DME (IF)	SCATT/8.50 DME (NOPT)	347.71 / 6.50	2000

MAP: 4.72 DME FIX

CLIMB TO 2500 DIRECT BVO VOR/DME AND HOLD.

## ADDITIONAL FLIGHT DATA:

HOLD N, RT, 167.00 INBOUND.  
CHART FAS OBST: 999 TREE 364244N/0960104W  
1189 AAO 364123N/0960154W  
CHART VDP AT 6.49 DME;  
DISTANCE VDP TO THLD 1.77 MILES.  
SCATT TO RW35: 3.10/45.

1. PT R SIDE OF COURSE 167.71 OUTBOUND 2500 FT WITHIN 10 MILES OF SCATT/8.50 DME (IAF)

2.

3. FAC 347.71 FAF SCATT/8.50 DME DIST FAF TO MAP - THLD 3.784. MIN. ALT SCATT 2000, JISAX/7.00 DME 15008. MSA FROM: BVO VOR/DME 080-260 3100, 260-080 2600

MAG VAR: 8E

EPOCH YEAR: 1965

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A			STANDARD @					
CATEGORY ==>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-35	1320	1	609	1320	1	609	1320	1 3/4	609	1320	2	609			
CIRCLING	1400	1	689	1400	1	689	1400	2	689	1400	2 1/4	689			

## NOTES:

CHART NOTE: CIRCLING NA EAST OF RWY 17-35.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TULSA INTERNATIONAL ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET AND S-35 CAT C/D VISIBILITY 1/4 MILE, CIRCLING CAT B/C/D VISIBILITY 1/4 MILE.

CHART NOTE: VDP NA WHEN USING TULSA INTERNATIONAL ALTIMETER SETTING.

@ CAT D 800-2 1/4

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE BARTLESVILLE, OK	ELEVATION: 711	TDZE: 711	FACILITY IDENTIFIER: BVO	PROCEDURE NO./ AMDT NO.: VOR/DME RWY 35, AMDT 6  DEC 20 2007	SUP		
	AIRPORT NAME:	AMDT 5A					
	BARTLESVILLE MUNI	DATE 11/02/2000					

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE

BARTLESVILLE, OK

ELEVATION: 711 TDZE: 711

AIRPORT NAME:

BARTLESVILLE MUNI

FACILITY  
IDENTIFIER:  
BVO

PROCEDURE NO./AMDT NO.:

VOR/DME RWY 35, AMDT 6

DEC 20 2007

SUP:

AMDT: 5A

DATED: 11/02/2000