

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1. PT	L	SIDE OF COURSE	051.14	OUTBOUND	5000	FT WITHIN	10	MILES OF	MAF VORTAC	(IAF)
2.										
3. FAC	231.14	FAF	ECTOR INT/MAF VORTAC 5.00 DME			DIST FAF TO MAP		5.70	THLD	
4. MIN. ALT	MAF VORTAC 5000, ECTOR 4500									
8. MSA FROM:	MAF VORTAC 5100									
										MAG VAR: 11E
										EPOCH YEAR: 1965

[illegible]

CHART NOTE: CIRCLING NA S OF RWYS 2 AND 34.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USED MIDLAND INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.
CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON MAF VORTAC AIRWAY RADIALS 357 CW 102.

QUALITY
SERVICES

FAA FORM 8260-5 / December 2002 (computer generated) PAGE 1 OF 1 PAGES