

**Federal Aviation
Administration**

Transmittal Letter 21-15

MAY 28, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/15/2021	MN	Marshall	Southwest Minnesota Rgnl	1/9866	5/12/2021	VOR RWY 12, Amdt 8B

Airac Date: 15 JULY 2021

FDC 1/9866 MML IAP SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD, MARSHALL, MN. VOR RWY 12, AMDT 8B... APT ELEV 1183. TDZE 1183. S-12 ALL CATS HAT 577, CAT C VIS 1 1/4. CIRCLING CAT A/B HAA 577, CAT C MDA 1820/HAA 637, CAT D MDA 1840/HAA 657. CIRCLING CAT C VIS 1 3/4. CEGUL FIX MINIMUMS: S-12 ALL CATS HAT 377, CAT C/D VIS 3/4. CIRCLING CAT A/B HAA 457, CAT C MDA 1820/HAA 637, CAT D MDA 1840/HAA 657. CIRCLING CAT C VIS 1 3/4. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TRACY MUNI ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET, S-12 CAT C/D VISIBILITY 1/8, CIRCLING CAT C/D VISIBILITY 1/4 SM; CEGUL FIX MINIMUMS: INCREASE CIRCLING C/D VISIBILITY 1/4 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE CEGUL FIX MINIMUMS S-12 CAT D VISIBILITY TO 1 1/4 MILE. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-12 CAT C/D VISIBILITIES TO 1 5/8 SM, CEGUL FIX MINIMUMS: S-12 CAT C/D VISIBILITY TO 1 SM. CHART NOTE: FOR INOPERATIVE ALS WHEN USING TRACY ALTIMETER SETTING INCREASE S-12 CAT C/D VISIBILITIES TO 1 3/4 SM. THIS IS VOR RWY 12, AMDT 8C. 2105041243-PERM