

**Federal Aviation
Administration**

Transmittal Letter 21-18

JULY 9, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/12/2021	SC	Orangeburg	Orangeburg Muni	1/7864	6/25/2021	RNAV (GPS) RWY 35, Amdt 1B

AIRAC Date: 12 AUGUST 2021

FDC 1/7864 OGB IAP ORANGEBURG MUNI, ORANGEBURG, SC. RNAV (GPS) RWY 35, AMDT 1B... LNAV/VNAV VIS 7/8 ALL CATS. LNAV VIS CAT C/D 1 1/8. CIRCLING CAT C/D MDA 1040/HAA 845, CAT C VIS 2 1/2, CAT D VIS 2 3/4. CHANGE UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. DELETE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. CHANGE CIRCLING NOTE TO READ: CIRCLING RWY 17 NA AT NIGHT. CHANGE BARO-VNAV NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING COLUMBIA METRO ALTIMETER SETTING. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LPV. CHART NOTE: FOR INOPERATIVE ALS, INCREASE CAT A/B VISIBILITY TO 1 SM. CHANGE NOTE READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLUMBIA METRO ALTIMETER SETTING AND INCREASE LPV DA TO 515 FEET AND ALL VISIBILITIES 1/8 SM, INCREASE LNAV/VNAV DA TO 618 FEET AND ALL VISIBILITIES 1/4 SM, INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C/D 1/4 SM, AND CIRCLING VISIBILITY CAT C/D 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 900- 2 1/2, CAT D 900-2 3/4; NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 35, AMDT 1C. 2106221241-PERM