

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: GASPE  CLIMBING LEFT TURN TO 4300 DIRECT BACAP AND HOLD.  ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1692 TREE 452915N/0683836W
DIPEY (IAF)	BACAP (NOPT) (FB)	073.31 / 6.00	4300	
APOCO (IAF)	BACAP (NOPT) (FB)	253.47 / 6.00	4300	
BACAP (IF/IAF)	CADEL (FB)	163.39 / 6.00	3400	
THIS IS A CORRECTED COPY OF THIS PROCEDURE PUBLISHED IN TL09-04.				

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD N BACAP, RT, 163.39 INBOUND, 4300 FT. IN LIEU OF PT (IAF)
- FAC: 163.44 FAF: CADEL DIST FAF TO MAP: 6.00 THLD:
- MIN. ALT: BACAP 4300, CADEL 3400
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH:
- MSA FROM:

MAG VAR: 18W

EPOCH YEAR: 1995

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N	A	X								
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	2140	1 1/4	1112	2280	1 1/2	1252	2280	3	1252		NA				

NOTES:  
CHART NOTE: DME/DME RNP-0.3 NA. ←  
CHART NOTE: PROCEDURE NA AT NIGHT.  
CHART NOTE: USE GREENVILLE MUNI ALTIMETER SETTING; WHEN NOT RECEIVED, USE BANGOR ALTIMETER SETTING AND INCREASE ALL MDA 240 FEET.

CITY AND STATE GREENVILLE, ME	ELEVATION: 1028 TDZE: AIRPORT NAME: GREENVILLE SPB	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, ORIG 12 MAR 2009	SUP: AMDT: NONE DATED
----------------------------------	--	------------------------------	---	-----------------------------

QUALITY  
CHECKED

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## TAA

	FROM	TO	ALT
1.	073/30 CW 253/30 (NOPT)	073/10 CW 253/10	5500
2.	073/10 CW 253/10	BACAP (IF/IAF) (FB)	4300
3.	253/30 CW 343/30	APOCO (IAF) (FB)	5500
4.	343/30 CW 073/30	343/15 CW 073/15	5900
5.	343/15 CW 073/15	DIPEY (IAF) (FB)	5500

CITY AND STATE

GREENVILLE, ME

ELEVATION: 1028 TDZE:

AIRPORT NAME:

GREENVILLE SPB

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS)-B, ORIG

12 MAR 2009

SUP:

AMDT: NONE

DATED:

QUALITY  
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

CITY AND STATE  GREENVILLE, ME	ELEVATION: 1028    TOZE:  AIRPORT NAME:  GREENVILLE SPB	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  RNAV (GPS)-B, ORIG  12 MAR 2009	SUP:
				AMDT:    NONE
				DATED:

QUALITY  
CHECK

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	APOCO	APOCO	010	IAF	IF		FB				
	APOCO	BACAP	020		TF		FB	1.0	253.5 (236T)	006.0	04300
	BACAP	BACAP	010		HF	R	FB		163.4 (145T)	005.0	04300
	DIPEY	DIPEY	010	IAF	IF		FB				
	DIPEY	BACAP	020		TF		FB	1.0	073.3 (055T)	006.0	04300
		BACAP	010	FACF	IF		FB				04300
		CADEL	020	PAF	TF		FB	0.5	163.4 (145T)	006.0	03400
		GASPE	030	MAP	TF		FO	0.3	163.4 (145T)	006.0	02280

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	BACAP	040		DF	L	FO	1.0			04300
	BACAP	050		HM	R	FO	2.0	163.4 (145T)	005.0	04300

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	APOCO	N454214.35	W0693919.90	N4542.239	W06939.332
	BACAP	N453850.13	W0694622.69	N4538.836	W06946.378
	CADEL	N453353.80	W0694131.62	N4533.897	W06941.527
	DIPEY	N453525.48	W0695324.62	N4535.425	W06953.410
	GASPE	N452857.28	W0693641.39	N4528.955	W06936.690

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH

CITY AND STATE  
**GREENVILLE, ME**

ELEVATION: 1028 TDZE:  
 AIRPORT NAME:  
**GREENVILLE SPB**

FACILITY  
 IDENTIFIER:  
**RNAV**

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
**RNAV (GPS)-B, ORIG**  
**12 MAR 2009**

SUP:  
 AMDT: **NONE**  
 DATED: