

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibility which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW18 CLIMB TO 3100 DIRECT GUBFO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 359.04 INBOUND. CHART FAS OBST: 358 TREE 360923N/0905456W DISTANCE TO THLD FROM 200 HATH: 0.49 NM. CHART VDP AT 0.95 MILES TO RW18* *LNAV ONLY. WAAS CHANNEL # 65925 REFERENCE PATH ID: W18A LTP HAE: 55.1 M	
EYPEB (IF/IAF)	YOFOB (FB)	179.04 / 6.80	1900		
YOFOB (FAF)	ROFKI/1.60 NM TO RW18 (FB)	179.04 / 3.40			
ROFKI/1.60 NM TO RW18	RW18 (MAP) (FO)	179.04 / 1.60			
RW18 (MAP)	473 MSL	179.04	3100		
473 MSL	GUBFO (FO)				
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD N EYPEB, RT, 179.04 INBOUND, 2700 FT. IN LIEU OF PT (IAF) 3. FAC: 179.04 FAF: YOFOB DIST FAF TO MAP: 4.97 THLD: 4.97 4. MIN. ALT: EYPEB 2700, YOFOB 1900, ROFKI/1.60 NM TO RW18 820* 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: 1900 GS ALT AT: YOFOB 1900 OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS CLEAR 8. MSA FROM: <u> </u>				MAG VAR: 1E EPOCH YEAR: 2000	
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A		
CATEGORY =====>			STANDARD @		
	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LPV DA	473	3/4	200	473	3/4
LNAV/VNAV DA	523	3/4	250	523	3/4
LNAV MDA	620	3/4	347	620	7/8
CIRCLING	760	1	481	760	1 1/2
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 42C (107F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING AND INCREASE ALL DA 54 FEET AND ALL MDA 60 FEET; INCREASE LNAV/VNAV ALL CATS (SEE FORM 8260-10)					
CITY AND STATE		ELEVATION: 279 THRE: 273		FACILITY IDENTIFIER: RNAV	
WALNUT RIDGE, AR		AIRPORT NAME: WALNUT RIDGE RGNL		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1 20 OCT 2011	
				SUP: AMDT: ORIG-A DATED 08/28/2008	

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

VISIBILITY 1/4 MILE AND LNAV CAT C AND D VISIBILITY 1/8 MILE.

CHART NOTE: FOR INOPERATIVE ODALS, INCREASE LPV ALL CATS AND LNAV/VNAV ALL CATS VISIBILITY TO 3/4 MILE AND LNAV CAT C AND D VISIBILITY TO 1 MILE.

CHART NOTE: WHEN USING JONESBORO ALTIMETER SETTING; FOR INOPERATIVE ODALS, INCREASE LPV ALL CATS VISIBILITY TO 7/8 MILE, LNAV/VNAV ALL CATS VISIBILITY TO 1 MILE AND LNAV CAT C AND D VISIBILITY TO 1 1/8 MILE.

CHART NOTE: BARO-VNAV AND VDP NA WITH JONESBORO ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	089/30 CW 269/30 (NOPT)	EYPEB (IF/IAF) (FB)	2700
2.	269/30 CW 089/30	EYPEB (IF/IAF) (FO)	3100

CITY AND STATE

WALNUT RIDGE, AR

ELEVATION: 279

THRE: 273

AIRPORT NAME:

WALNUT RIDGE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, AMDT 1

20 OCT 2011

SUP:

AMDT: ORIG-A

DATED: 08/28/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KARG
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	360757.8450N
LTP/FTP LONGITUDE	0905523.7705W
LTP/FTP ELLIPSOIDAL HEIGHT	+00551
FPAP LATITUDE	360628.6200N
FPAP LONGITUDE	0905523.8500W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

A265282B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00833
FPAP ORTHOMETRIC HEIGHT	+00833

CITY AND STATE
WALNUT RIDGE, AR

ELEVATION: 279 THRE: 273
AIRPORT NAME:
WALNUT RIDGE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 18, AMDT 1
20 OCT 2011

SUP:
AMDT: ORIG-A
DATED: 08/28/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)[illegible]

SUSAEAENRT	EYPEB	K40	W	N36194485W090552316	W0002	NAR	EYPEB
SUSAEAENRT	GUBFO	K40	W	N35550913W090552443	W0002	NAR	GUBFO
SUSAEAENRT	ROFKI	K40	W	N36093399W090552369	W0002	NAR	ROFKI
SUSAEAENRT	YOFOB	K40	W	N36125628W090552351	W0002	NAR	YOFOB

[illegible]

SUSAP KARGK4AARG	0	060YHN36072880W090553040E001000279	1800018000C	MNAR	WALNUT RIDGE RGNL
------------------	---	------------------------------------	-------------	------	-------------------

[illegible]

SUSAP	KARGK4FR18	AEYPEB	010EYPEBK4EA0EE	AR	HF	17900040	+	02700	18000		A	JS
SUSAP	KARGK4FR18	R	010EYPEBK4EA0E	I	IF		+	02700	18000		A	JS
SUSAP	KARGK4FR18	R	020YOF0BK4EA1E	F	051TF	17900068	+	01900			A	JS
SUSAP	KARGK4FR18	R	020YOF0BK4EA2WALPV		ALNAV/VNAV ALNAV							JS
SUSAP	KARGK4FR18	R	021ROFKIK4EA0E	S	031TF	17900034	V	0082000828		-300	A	JS
SUSAP	KARGK4FR18	R	030RW18	K4PG0GY	M 031TF	17900016		00318		-300	A	JS
SUSAP	KARGK4FR18	R	040		0 M CA	1790	+	00473			A	JS
SUSAP	KARGK4FR18	R	050GUBFOK4EA0EY		DF		+	03100			A	JS
SUSAP	KARGK4FR18	R	060GUBFOK4EA0EE	R	HM	35900040	+	03100			A	JS

[illegible]

SUSAP KARGK4GRW18 0050011790 N36075785W090552377+0000 +0055100273000045150R

[illegible]

SUSAP	KARGK4PR18	RW18	001	0000W18A0N3607578450W09055237705+005510300N3606286200W09055238500106751224000450F400350A265282B
SUSAP	KARGK4PR18	RW18	002E	+00833+00833LPV 65925

CITY AND STATE
WALNUT RIDGE, AR

ELEVATION: 279 THRE: 273
AIRPORT NAME:
WALNUT RIDGE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 18, AMDT 1
20 OCT 2011

SUP:	
AMDT:	ORIG-A
DATED:	08/28/2008