

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: OCF VORTAC
				CLIMB TO 2000 VIA OCF VORTAC R-355 TO LEJKO INT/OCF 10.00 DME AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD S, RT, 355.48 INBOUND. CHART FAS OBST: 321 TOWER 290515N/0821102W CHART VDP AT 2.74 DME; DISTANCE VDP TO THLD 1.68 MILES. FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD.

1. PT R SIDE OF COURSE 173.58 OUTBOUND 1700 FT WITHIN 10 MILES OF OCF VORTAC (IAF)
 2. _____
 3. FAC 353.58 FAF _____ DIST FAF TO MAP _____ THLD _____
 4. MIN. ALT _____
 8. MSA FROM: OCF VORTAC 2500

MAG VAR: 0E

EPOCH YEAR: 1970

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A			STANDARD @						
CATEGORY =====>		A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-36		640	3/4	560	640	3/4	560	640	1	560	640	1 1/4	560			
CIRCLING		640	1	551	640	1	551	640	1 1/2	551	640	2	551			

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GAINESVILLE ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET; INCREASE S-36 CATS C AND D, AND CIRCLING CAT C VISIBILITY 1/4 MILE.
 CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-36 CATS A AND B VISIBILITY TO 1 MILE.
 CHART NOTE: FOR INOPERATIVE MALSR WHEN USING GAINESVILLE ALTIMETER SETTING, INCREASE S-36 CATS A SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE OCALA, FL	ELEVATION: 89 TDZE: 80 AIRPORT NAME: OCALA INTL-JIM TAYLOR FLD	FACILITY IDENTIFIER: OCF	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 36, AMDT 18 15 JAN 2009	SUP AMDT 17 DATE 08/10/2000
------------------------------------	---	------------------------------------	--	---

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

AND B VISIBILITY TO 1 MILE.

CHART NOTE: VDP NA WHEN USING GAINESVILLE ALTIMETER SETTING.

CITY AND STATE

OCALA, FL

ELEVATION: 89 TDZE: 80

AIRPORT NAME:

OCALA INTL-JIM TAYLOR FLD

FACILITY
IDENTIFIER:

OCF

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 36, AMDT 18

15 JAN 2009

SUP:

AMDT: 17

DATED: 08/10/2000