

**Federal Aviation
Administration**

Transmittal Letter 24-14

May 10, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT NAME	FDC NUMBER	FDC DATE	PROCEDURE NAME
6/13/2024	GA	Jefferson	Jackson County	4/8141	5/6/2024	RNAV (GPS) RWY 35, Amdt 3

AIRAC Date: 13 JUNE 2024

FDC 4/8141 JCA IAP JACKSON COUNTY, JEFFERSON, GA. RNAV (GPS) RWY 35, AMDT 3... LPV VIS ALL CATS 7/8. LNAV/VNAV VIS ALL CATS 7/8. CIRCLING CATS C/D MDA 1580/HAT 629. CIRCLING CAT C VISIBILITY 1 3/4. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK FROM VDP 1 NM TO RW35. CHANGE HELICOPTER NOTE TO READ: RWY 35 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WINDER ALTIMETER SETTING; INCREASE LPV DA TO 1232 FEET AND VISIBILITY ALL CATS 1/8 SM; INCREASE LNAV/VNAV DA TO 1241 FEET AND VISIBILITY ALL CATS 1/8 SM; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CATS C/D 1/8 SM. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. ALTERNATE MINIMUMS: STANDARD; NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 35, AMDT 3A. 2405031603-PERM