

**Federal Aviation
Administration**

Transmittal Letter 21-01

November 13, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/31/2020	MN	Waseca	Waseca Muni	0/0401	10/29/2020	RNAV (GPS) RWY 15, Amdt 1A

AIRAC Date: 31 DECEMBER 2020

FDC 0/0401 ACQ IAP WASECA MUNI, WASECA, MN. RNAV (GPS) RWY 15, AMDT 1A... LNAV/VNAV DA 1516/HAT 389, CATS A/B VIS 1 1/8. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OWATONNA ALTIMETER SETTING AND INCREASE ALL DA 34 FEET AND ALL MDA 40 FT; INCREASE LNAV AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OWATONNA ALTIMETER SETTING AND INCREASE ALL DA 34 FEET AND ALL MDAS 40 FT; INCREASE LNAV/VNAV VISIBILITY ALL CATS 1/8 SM, LNAV AND CIRCLING CAT C VISIBILITY 1/4 SM. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. CHART NOTE: RWY 15 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. THIS IS RNAV (GPS) RWY 15, AMDT 1B. 2008311237-PERM