

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT AJAYS ON V221 NORTHBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FAXIG ON V14 SOUTHWEST BOUND.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FORT WAYNE INTL ALTIMETER SETTING AND

INCREASE LPV DA TO 1255, LNAV/VNAV DA TO 1320 AND ALL MDA 100 FEET, INCREASE LPV ALL CATS

VISIBILITY 1/8 MILE, LNAV/VNAV ALL CATS AND LNAV CAT C VISIBILITY 3/8 MILE AND CIRCLING CAT C

VISIBILITY 1/4 MILE.

CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 9 PROCEDURE NA AT NIGHT.

CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 27 NA AT NIGHT.

QUALITY
2
CHECKED

CITY AND STATE

PORTLAND, IN

ELEVATION: 925

THRE: 913

AIRPORT NAME:

PORTLAND MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 9, AMDT 1

20 OCT 2011

SUP:

AMDT: ORIG

DATED: 07/31/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KPLD
RUNWAY	RW09
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W09A
LTP/FTP LATITUDE	402705.1680N
LTP/FTP LONGITUDE	0845946.3370W
LTP/FTP ELLIPSOIDAL HEIGHT	+02448
FPAP LATITUDE	402707.3300N
FPAP LONGITUDE	0845749.6600W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

33E61BF3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02784
FPAP ORTHOMETRIC HEIGHT	+02784

QUALITY
2
CHECKED

CITY AND STATE PORTLAND, IN	ELEVATION: 925 THRE: 913 AIRPORT NAME: PORTLAND MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 20 OCT 2011	SUP:
				AMDT: ORIG
				DATED: 07/31/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KPLDK5FR09	AAJAYS	010AJAYSK5EA0E	A	IF					18000		A	JS
SUSAP	KPLDK5FR09	AAJAYS	020DIYECK5EA0EE	B	010TF		15340091	+	02500			A	JS
SUSAP	KPLDK5FR09	ADIYEC	010DIYECK5EA0EE	AR	HF		09150040	+	02500	18000		A	JS
SUSAP	KPLDK5FR09	AFAXIG	010FAXIGK5EA0E	A	IF					18000		A	JS
SUSAP	KPLDK5FR09	AFAXIG	020DIYECK5EA0EE	B	010TF		01210083	+	02500			A	JS
SUSAP	KPLDK5FR09	R	010DIYECK5EA0E	I	IF			+	02500	18000		A	JS
SUSAP	KPLDK5FR09	R	020CAXUVK5EA1E	F	051TF		09150061	+	02000		RW09	K5PGA	JS
SUSAP	KPLDK5FR09	R	020CAXUVK5EA2WALPV			ALNAV/VNAV	ALNAV						JS
SUSAP	KPLDK5FR09	R	030RW09	K5PGOGY	M	031TF	09160033		00953	-300		A	JS
SUSAP	KPLDK5FR09	R	040		O	M	0916	+	01163			A	JS
SUSAP	KPLDK5FR09	R	050MAPOLK5EA0EY		DF				03000			A	JS
SUSAP	KPLDK5FR09	R	060MAPOLK5EA0EE	R	HM		27180040	+	03000			A	JS

[illegible][illegible]

012 QUALITY
CHECKED

CITY AND STATE PORTLAND, IN	ELEVATION: 925 THRE: 913 AIRPORT NAME: PORTLAND MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 20 OCT 2011	SUP:
				AMDT: ORIG
				DATED: 07/31/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE PORTLAND, IN	ELEVATION: 925 THRE: 913	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 20 OCT 2011	SUP:	
	AIRPORT NAME: PORTLAND MUNI			AMDT:	ORIG
				DATED:	07/31/2008