

NDB

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: MZH NDB
BARUM INT	MZH NDB	251.82/23.91	4000	CLIMB TO 3000, THEN RIGHT TURN DIRECT MZH NDB AND HOLD.
				ADDITIONAL FLIGHT DATA:
				HOLD SW, RT, 041 INBOUND.
				FAS OBST: 1449 POWER LINE 462032 / 925721.
				FAC 456R RWY C/L EXTENDED 3000 FROM THLD.
				CHART: AWOS-3

1. PT L SIDE OF COURSE 221.00 OUTBOUND 3000 FT WITHIN 10 MILES OF MZH NDB (IAF)

2.

3. FAC 041.00 FAF _____ DIST FAF TO MAP _____ THLD _____

4. MIN. ALT -

8. MSA FROM: MZH NDB 2800

MAG VAR: 2 E

EPOCH YEAR: 95

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15 FOR THIS AIRPORT				ALTERNATE: N A		X						
CATEGORY =====>		A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA
S-4		1800	1	724	1800	1	724		NA			NA				
CIRCLING		1800	1	724	1800	1	724		NA			NA				

NOTES:

CITY AND STATE

MOOSE LAKE, MN

ELEVATION:

1076

TDZE:

1076

AIRPORT NAME:

MOOSE LAKE CARLTON COUNTY

FACILITY
IDENTIFIER:

MZH

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

 26 FEB 98
 NDB OR GPS RWY 4, AMDT 1

SUP

AMDT ORIG-B

DATE 08/21/96