

**Federal Aviation
Administration**

Transmittal Letter 22-03

December 10, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/27/2022	KS	Hays	Hays Rgnl	1/7864	11/18/2021	RNAV (GPS) RWY 34, Amdt 2

AIRAC Date: 27 JANUARY 2022

FDC 1/7864 HYS IAP HAYS RGNL, HAYS, KS. RNAV (GPS) RWY 34, AMDT 2... CIRCLING CAT A MDA 2480/HAA 481, CAT C MDA 2560/HAA 561, CAT D MDA 2680/HAA 681, VIS CAT D 2 1/4. CHART NOTE: CIRCLING NA FOR CAT D NW OF RWY 4 AND W OF RWY 16. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RUSSELL ALTIMETER SETTING: INCREASE LPV DA TO 2263 FEET; INCREASE LNAV/VNAV DA TO 2565 FEET AND VISIBILITY ALL CATS 1/4 SM; INCREASE ALL MDA 80 FEET AND VISIBILITY LNAV CAT C AND CIRCLING CAT C AND D 1/4 SM. THIS IS RNAV (GPS) RWY 34, AMDT 2A. 2111152126-PERM