



U.S. Department
of Transportation
Federal Aviation
Administration

DEPARTURE PROCEDURES/TAKEOFF MINIMUMS

Book

Headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise specified. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH → ☒ AAT ☐ ATA ☐ ALPA ☐ AOPA ☐ NBAA ☐ APA ☒ OTHER (Specify) AVN-220, AGL-220
ZAU ARTCC, AMGR

TAKEOFF MINIMUMS:

Rwys 9, 18, 27, 36: 300-1.

TAKEOFF OBSTACLES:

Rwys 18, 27: 820 Tower 405628/871115.

Rwys 9, 18, 36: 815 Tower 405645/870845.

969 Tower 405550/870810.

1065 Tower 405530/870910.

Rwy 9, 36: 999 Tower 405810/870909.

IFR DEPARTURE PROCEDURES:

Rwys 9, 18, 27, 36: Climb to 1100 on runway heading before proceeding on course.

*Concurrent with NDB Rwy 18, Amdt 3.

DEVELOPED BY		APPROVED BY	
SIGNATURE R. H. BARNES	DATE 24 AUG 1987 FIFO BTL	SIGNATURE GERALD W. HILL, Manager, BTL FIFO	DATE 24 AUG 1987
CITY AND STATE Rensselaer, IN	AIRPORT Jasper County	EFFECTIVE DATE *	AMDT. NO. 1