

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
ILS STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KMCI	<u>PROCEDURE NAME</u> ILS OR LOC RWY 19L	<u>ORIGINAL/AMENDMENT</u> 2C	<u>CITY</u> KANSAS CITY	<u>STATE</u> MO		
<u>AIRPORT ELEVATION</u> 1027	<u>TDZE</u> 995	<u>SUPERSEDED</u> ILS OR LOC RWY 19L	<u>ORIGINAL/AMENDMENT</u> 2B	<u>DATED</u> 12/07/2017	<u>MAG VAR</u> 2E	<u>EPOCH YEAR</u> 2015
<u>FACILITY</u> I-DYH	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 2 DECEMBER 2021	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
STJ VORTAC		TUSKG INT/17.32 DME/RADAR					141.95	27.71	6000
TUSKG INT/17.32 DME/RADAR	IAF	AYRMN/14.18 DME/RADAR					190.95	3.14 (I-DYH)	5000
AYRMN/14.18 DME/RADAR		MGEEEE/11.04 DME/RADAR					190.95	3.14 (I-DYH)	4000
MGEEEE/11.04 DME/RADAR	IF	ROMNS/7.90 DME/RADAR					190.95	3.14 (I-DYH)	3000
ROMNS/7.90 DME/RADAR		MAZOU/6.64 DME/RADAR					190.95	1.26 (I-DYH)	2600

MISSED APPROACH

MAP:

ILS: DA
LOC: 4.91 NM AFTER MAZOU/6.64 DME/RADAR OR AT I-DYH 1.74 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 4000 DIRECT ANX VORTAC AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS (DO NOT CHART):

CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 4000 ON HEADING 080 AND MCI VORTAC R-089 TO LYMES INT/MCI 29.18 DME AND HOLD. (DME REQUIRED).





CHANGES - REASONS

1. REPLACED FIX GAYLY WITH FIX TUSKG - HONORARY FIX NAME REQUEST.
2. REPLACED FIX YOVNU WITH FIX AYRMN - HONORARY FIX NAME REQUEST.
3. REPLACED FIX ZASBO WITH FIX MGEED - HONORARY FIX NAME REQUEST.
4. REMOVED *LOC ONLY AND ASSOCIATED * SYMBOL - IAW 8260.19I 1-1-5F(12).
5. ADDED "CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 19L CAT C/D VISIBILITY TO RVR 4500." - UPDATED VISCHECK VALUES AND IAW 8260.19I 8-6-11O(3)(D).
6. ADDED "CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON STJ VORTAC AIRWAY RADIALS 114 CW 203." - IAW 8260.19I 8-2-5E AND 8260.3E 2-3-1A(1).
7. REMOVED PAIRED DME I-DYH - 8260.19I 8-2-6C(1).
8. MOVED CHART NOTE "DME OR RADAR REQUIRED" TO EQUIPMENT REQUIREMENTS NOTES - 8260.19I 8-6-8A(2).
9. MODIFIED S-LOC 19L CAT C & D VISIBILITY FROM "2600" TO "2400" - UPDATED VISCHECK RESULTS.

COORDINATED WITH:

A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒ **OTHER:** ZKC, MCI APP CON, MCI ATCT, AMGR

FLIGHT CHECKED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED
07/07/2021, SUBJECT: GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT
INSPECTION/VALIDATION

DEVELOPED BY

JASON KRETSCHMER (CURTIS MALONE)

APPROVED BY

MARLON ROBINSON

Digitally signed by

JASON KRETSCHMER

Oct 07, 2021

Digitally signed by

JASON KRETSCHMER

Oct 07, 2021

OFFICE

Digitally signed by

JASON KRETSCHMER

Oct 07, 2021

OFFICE

AJV-A421

OFFICE

AJV-A420

DATE**DATE**

07/26/2021

DATE**TITLE**

MANAGER