

<b>RNAV - STANDARD</b> <b>INSTRUMENT APPROACH PROCEDURE</b> <b>TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>																
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW04  CLIMB TO 2700 DIRECT ESEGE AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD NE, RT, 224.15 INBOUND. CHART FAS OBST: 359 TREE 360702N/0905635W DISTANCE TO THLD FROM 250 HATH: 0.64 NM. CHART VDP AT 0.93 MILES TO RW04* *LNAV ONLY. WAAS CHANNEL # 77825 REFERENCE PATH ID: W04A LTP HAE: 56.9 M						
XIHAM (IF/IAF)		ZUPTA (FB)		043.95 / 6.80				1900								
ZUPTA (FAF)		TILVE/1.50 NM TO RW04 (FB)		044.01 / 3.45												
TILVE/1.50 NM TO RW04		RW04 (MAP) (FO)		044.04 / 1.50												
RW04 (MAP)		529 MSL		044.04				2700								
529 MSL		ESEGE (FO)														
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD SW XIHAM, RT, 043.95 INBOUND, 2700 FT. IN LIEU OF PT (IAF) 3. FAC: <u>044.01</u> FAF: <u>ZUPTA</u> DIST FAF TO MAP: <u>4.95</u> THLD: <u>4.95</u> 4. MIN. ALT: <u>XIHAM 2700, ZUPTA 1900, TILVE/1.50 NM TO RW04 800*</u> 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>1900</u> GS ALT AT: <u>ZUPTA 1900</u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>45.0</u> 34:1 IS CLEAR 8. MSA FROM: <u>      </u>										MAG VAR: 1E EPOCH YEAR: 2000						
<b>MINIMUMS</b>																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	529	3/4	250	529	3/4	250	529	3/4	250	529	3/4	250				
LNAV/VNAV DA	529	3/4	250	529	3/4	250	529	3/4	250	529	3/4	250				
LNAV MDA	620	1	341	620	1	341	620	1	341	620	1	341				
CIRCLING																
	760	1	481	760	1	481	760	1 1/2	481	840	2	561				
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING JONESBORO ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 42C (107F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VDP NA WITH JONESBORO ALTIMETER SETTING. (SEE FORM 8260-10)																
CITY AND STATE		ELEVATION: 279		THRE: 279		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:				
WALNUT RIDGE, AR		AIRPORT NAME:		WALNUT RIDGE RGNL		RNAV		RNAV (GPS) RWY 4, ORIG				AMDT: NONE				
								20 OCT 2011				DATED				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING AND INCREASE ALL DA 54 FEET AND ALL MDA 60 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE AND LNAV CAT C AND D VISIBILITY 1/8 MILE.

TAA

	FROM	TO	ALT
1.	314/30 CW 134/30 (NOPT)	314/6 CW 134/6	3100
2.	314/6 CW 134/6	XIHAM (IF/IAF) (FB)	2700
3.	134/30 CW 314/30	XIHAM (IF/IAF) (FO)	3100

CITY AND STATE

WALNUT RIDGE, AR

ELEVATION: 279

THRE: 279

AIRPORT NAME:

WALNUT RIDGE RGNL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4, ORIG

20 OCT 2011

SUP:

AMDT: NONE

DATED:

## U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KARG
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	360648.8290N
LTP/FTP LONGITUDE	0905601.1875W
LTP/FTP ELLIPSOIDAL HEIGHT	+00569
FPAP LATITUDE	360751.8600N
FPAP LONGITUDE	0905443.3500W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0920
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

FD403B0F

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00851
FPAP ORTHOMETRIC HEIGHT	+00851

CITY AND STATE WALNUT RIDGE, AR	ELEVATION: 279      THRE: 279 AIRPORT NAME: WALNUT RIDGE RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG 20 OCT 2011	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KARGK4FR04	AXIHAM	010XIHAMK4EA0EE	AR	HF		04400040	+	02700	18000			A	JS
SUSAP KARGK4FR04	R	010XIHAMK4EA0E	I	IF			+	02700	18000			A	JS
SUSAP KARGK4FR04	R	020ZUPTAK4EA1E	F	051TF		04400068	+	01900				A	JS
SUSAP KARGK4FR04	R	020ZUPTAK4EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KARGK4FR04	R	021TILVEK4EA0E	S	031TF		04400035	V	0080000802		-300		A	JS
SUSAP KARGK4FR04	R	030RW04 K4PG0GY	M	031TF		04400015		00324		-300		A	JS
SUSAP KARGK4FR04	R	040	0	M	CA	0440	+	00529				A	JS
SUSAP KARGK4FR04	R	050ESEGEK4EA0EY		DF			+	02700				A	JS
SUSAP KARGK4FR04	R	060ESEGEK4EA0EE	R	HM		22420040	+	02700				A	JS

[illegible][illegible]

CITY AND STATE  
WALNUT RIDGE, AR

ELEVATION: 279                      THRE: 279  
AIRPORT NAME:  
WALNUT RIDGE RGNL

**FACILITY IDENTIFIER:**  
**RNAV**

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 4, ORIG  
20 OCT 2011

SUP:	
AMDT:	NONE
DATED:	