

**Federal Aviation  
Administration**

**Transmittal Letter 21-12**

**April 16, 2021**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/20/2021	AR	Walnut Ridge	Walnut Ridge Rgnl	1/2789	4/1/2021	RNAV (GPS) RWY 4, Orig-A

**AIRAC Date: 20 MAY 2021**

FDC 1/2789 ARG IAP WALNUT RIDGE RGNL, WALNUT RIDGE, AR. RNAV (GPS) RWY 4, ORIG-A... CIRCLING CATS A/B/C MDA 840/HAA 561, CIRCLING CAT D MDA 1000/HAA 721, VIS CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING AND INCREASE LPV AND LNAV/VNAV DA TO 583 FEET, AND ALL MDAS 60 FEET; INCREASE CIRCLING CATS C/D VISIBILITY 1/4 SM. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4 - NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 4, ORIG-B. 2103311446-PERM