

**Federal Aviation
Administration**

Transmittal Letter 22-23

September 16, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/3/2022	TX	Stamford	Arledge Fld	2/4031	9/9/2022	RNAV (GPS) RWY 17, Orig-B

AIRAC Date: 3 NOVEMBER 2022

FDC 2/4031 F56 IAP ARLEDGE FLD, STAMFORD, TX. RNAV (GPS) RWY 17, ORIG-B... AYOTI (IAF) TO COXAK
MINIMUM ALTITUDE 3300. ELUGY (IAF) TO COXAK MINIMUM ALTITUDE 3300. MINIMUM ALTITUDE COXAK
3300. CHANGE ALTIMETER SETTING NOTE TO READ: USE ABILENE RGNL ALTIMETER SETTING; WHEN
NOT RECEIVED USE BRECKENRIDGE ALTIMETER SETTING AN INCREASE ALL MDAS 40 FEET. CHART
NOTE: RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. COXAK MINIMUM
HOLDING ALTITUDE 3300. LNAV CAT C VISIBILITY 1 3/8. THIS IS RNAV (GPS) RWY 17, ORIG-C.
2208041441-PERM