

**Federal Aviation
Administration**

Transmittal Letter 22-01

November 12, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/30/2021	NC	Jacksonville	Albert J Ellis	1/4875	9/3/2021	ILS OR LOC RWY 5, Amdt 9B

AIRAC Date: 30 DECEMBER 2021

FDC 1/4875 OAJ IAP ALBERT J ELLIS, JACKSONVILLE, NC. ILS OR LOC RWY 5, AMDT 9B... CIRCLING CAT C/D MDA 720/HAA 627, CAT C VIS 1 3/4. OGOYO FIX MINIMUMS: CIRCLING CAT A MDA 540/HAA 447. CIRCLING CAT C/D MDA 720/HAA 627, VIS CAT C 1 3/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WILMINGTON ALTIMETER SETTING AND INCREASE ALL DA TO 382 FEET; INCREASE ALL MDAS 100 FEET AND VISIBILITY S-LOC 5 CATS C/D AND CIRCLING CATS C/D 1/4 SM; OGOYO FIX MINIMUMS: INCREASE VISIBILITY S-LOC 5 CATS C/D 3/8 SM AND CIRCLING CATS C/D 1/4 SM. THIS IS ILS OR LOC RWY 5, AMDT 9C. 2108241858-PERM