

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
FAY VOR/DME (IAF)	VIYUC/15.00 DME	151.52 / 15.00	2200
VIYUC/15.00 DME (IF)	SLITT/21.00 DME	151.52 / 6.00 (FAY R-152)	2200

MISSED APPROACH

MAP: 26.83 DME FIX

CLIMB TO 1000 THEN CLIMBING RIGHT TURN TO 2200 ON FAY R-152 TO SLITT/21.00 DME AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD NW, RT, 151.52 INBOUND.
 CHART FAS OBST: 492 TOWER 343732N/0783727W
 SLITT TO RW15: 3.28/43

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT VIYUC/15.00 DME
3. FAC 151.52 FAF SLITT/21.00 DME DIST FAF TO MAP THLD 5.83
4. MIN. ALT VIYUC 2200, SLITT 2200
8. MSA FROM: FAY VOR/DME 3200 (28 NM)

MAG VAR: 4W

EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @		
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-15	760	1	628	760	1 1/4	628	760	1 3/4	628	760	2	628			
CIRCLING	760	1	628	760	1 1/4	628	760	1 3/4	628	800	2	668			

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FAYETTEVILLE ALTIMETER SETTING AND INCREASE ALL MDA 80 FT AND INCREASE S-15 VISIBILITY CATS C AND D 1/4 MILE AND INCREASE CIRCLING SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
9
CHECKED

CITY AND STATE ELIZABETHTOWN, NC	ELEVATION: 132 TDZE: 132 AIRPORT NAME: CURTIS L BROWN JR FIELD	FACILITY IDENTIFIER: FAY	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 15, AMDT 2 23 SEP 2010	SUP AMDT 1 DATE 03/20/2003
--	---	------------------------------------	---	--

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.**VISIBILITY CAT C 1/4 MILE, AND CAT D 1/2 MILE.****CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FAY VOR/DME ON AIRWAY RADIALS 102 CW 178.**

QUALITY
9
CHECKED

CITY AND STATE

ELIZABETHTOWN, NC

ELEVATION: 132 TDZE: 132

AIRPORT NAME:

CURTIS L BROWN JR FIELD

FACILITY
IDENTIFIER:

FAY

PROCEDURE NO / AMDT NO / EFFECTIVE DATE:

VOR/DME RWY 15, AMDT 2

23 SEP 2010

SUP:

AMDT: 1

DATED: 03/20/2003