

**Federal Aviation
Administration**

Transmittal Letter 11-24

October 14, 2011

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
17-Nov-11	TX	Uvalde	Garner Field	1/4475	10/6/11	RNAV (GPS) RWY 33, ORIG

AIRAC Date: 17 NOVEMBER 2011

FDC 1/4475 UVA FI/P IAP GARNER FIELD, UVALDE, TX. RNAV (GPS) RWY 33, ORIG... ALTERNATE MINIMUMS STANDARD EXCEPT NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HONDO MUNI ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND INCREASE LNAV CAT C AND D AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHANGE NOTE GPS OR RNP-0.3 REQUIRED, DME/DME RNP-0.3 NA TO READ: DME/DME RNP-0.3 NA. THIS IS RNAV (GPS) RWY 33, ORIG-A.