

**Federal Aviation
Administration**

Transmittal Letter 18-22

September 7, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
11-Oct-18	PA	State College	University Park	8/6368	8/29/18	RNAV (GPS) RWY 24, Amdt 1

AIRAC Date: 11 OCTOBER 2018

FDC **8/6368** UNV IAP UNIVERSITY PARK, State College, PA. RNAV (GPS) RWY 24, AMDT 1... LNAV/VNAV DA 1619/HAT 401, VISIBILITY 3/4 ALL CATS. LNAV MDA 1640/HAT 422 ALL CATS. CIRCLING CAT C MDA 1940/HAA 709, CAT D MDA 2580/HAA 1349, VIS CAT C 2, CAT D 3. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLEARFIELD ALTIMETER SETTING: INCREASE LPV DA TO 1524 FEET AND LNAV/VNAV DA TO 1725 FEET AND VISIBILITY LNAV/VNAV ALL CATS 1/4 SM; INCREASE ALL MDAS 120 FEET AND VISIBILITY LNAV CATS C/D 3/8 SM AND CIRCLING CAT C 1/2 SM. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 1/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLEARFIELD ALTIMETER SETTING: INCREASE LPV DA TO 1524 AND LNAV/VNAV DA TO 1632 AND ALL MDA 120 FEET; INCREASE LPV ALL CATS VISIBILITY AND CIRCLING CAT C VISIBILITY 1/8 SM, AND INCREASE LNAV/VNAV ALL CATS VISIBILITY 3/8 SM, AND LNAV CAT C AND D AND CIRCLING CAT D VISIBILITY 1/4 SM. DELETE NOTE: FOR INOPERATIVE ALS, INCREASE LNAV CAT C/D VISIBILITY TO 1 1/8 SM. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA NOTE. CHART NOTE: FOR INOPERATIVE ALS WHEN USING CLEARFIELD ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 7/8 SM AND LNAV/VNAV ALL CATS TO 1 3/8 SM. DELETE NOTE: FOR

INOPERATIVE ALS WHEN USING CLEARFIELD ALTIMETER SETTING, INCREASE
LPV ALL CATS VISIBILITY TO 1 1/8 SM. CHART FAS OBST: 1336 TREE
405202N/0774916W. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 1400-3.
DELETE ALTERNATE MINIMUMS NOTE: @ NA WHEN LOCAL WEATHER NOT
AVAILABLE. THIS IS RNAV (GPS) RWY 24, AMDT 1A. 1806152024-PERM