

**Federal Aviation
Administration**

Transmittal Letter 21-07

February 5, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
3/25/2021	TX	Longview	East Texas Rgnl	0/6675	12/16/2020	RNAV (GPS) RWY 36, Amdt 1

25 MARCH 2021

FDC 0/6675 GGG IAP EAST TEXAS RGNL, LONGVIEW, TX. RNAV (GPS) RWY 36, AMDT 1...
CIRCLING CAT C MDA 980/HAA 614, CAT D MDA 1080/HAA 714, VISIBILITY CAT C 1 3/4
AND CAT D 2 1/4. DELETE NOTE: DME/DME RNP 0.3 NA. PBN REQUIREMENT NOTE: RNP
APCH - GPS. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN
LOCAL WEATHER NOT AVAILABLE. LNAV CATS C/D VISIBILITY 1 1/8. CHANGE ALTIMETER
NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GILMER
ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND LNAV AND CIRCLING CATS
C/D VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 36, AMDT 1A. 2011302030-PERM