

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SARASOTA	SIX	SRQ6.SRQ	FIVE	09/16/2016	<b>17 Apr 2025</b>

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**DP ROUTE DESCRIPTION:**

TAKEOFF RWY 14: CLIMB HEADING 139.38. EXPECT RADAR VECTORS TO JOIN ASSIGNED ROUTE, THENCE ...

TAKEOFF RWY 32: CLIMBING LEFT TURN TO INTERCEPT SRQ R-268 WESTBOUND OR AS ASSIGNED BY ATC. EXPECT RADAR VECTORS TO JOIN ASSIGNED ROUTE, THENCE...

...MAINTAIN 3000 OR AS ASSIGNED BY ATC. EXPECT CLEARANCE TO FILED ALTITUDE TEN MINUTES AFTER DEPARTURE.

**TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):**

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

**PBN REQUIREMENT NOTES:****EQUIPMENT REQUIREMENT NOTES:**

RADAR REQUIRED.

**PROCEDURAL DATA NOTES:**

RWY 32, TURBO-JET AIRCRAFT DO NOT TURN PRIOR TO DEPARTURE END OF RWY.

**TAKEOFF MINIMUMS:**

RWYS 4, 22: NA- ATC

RWY 14: STANDARD

RWY 32: STANDARD WITH ATC CLIMB OF 500 FT/NM TO 540.

**TAKEOFF OBSTACLES NOTES:**

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

**CONTROLLING OBSTACLES:****MSA:**

MSA FROM SRQ VOR/DME, 2800.

**LOST COMMUNICATIONS PROCEDURES:****ADDITIONAL FLIGHT DATA:**

CHART: TOP ALTITUDE: 3000

AIRPORT MV: SRQ W05/2010



AIRPORTS SERVED:

AIRPORT ID	CITY	STATE
SRQ	SARASOTA/BRADENTON INTL	FL

COMMUNICATIONS:

CHART: ATIS, SARASOTA TOWER, CLNC DEL, TAMPA DEP CON, GND CON

FIXES AND/OR NAVAIDS:

LAL VORTAC, ORL VORTAC, PIE VORTAC, RSW VORTAC, SRQ VORTAC, SZW VORTAC

REMARKS:

ABBREVIATED AMENDMENT.  
MSA OBTAINED FROM PUBLISHED APPROACH PROCEDURE AT SRQ.

FLIGHT INSPECTED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

SIGNATURE

Digitally signed by

CASIMIR L TABAKA

OFFICE

DATE

DEVELOPED BY

CASIMIR L. TABAKA (CHRISTOPHER D. WILKINSON)

SIGNATURE

Nov 25, 2024  
Digitally signed by

CASIMIR L TABAKA

OFFICE

AJV-A432

DATE

09/30/2024

APPROVED BY

CASIMIR L. TABAKA

SIGNATURE

Digitally signed by

CASIMIR L TABAKA

OFFICE

AJV-A432

DATE

Nov 25, 2024

TITLE

MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A ☒ ALPA ☒ AOPA ☒ APA ☒ HAI ☐ NBAA ☒ OTHER: ZMA, ZJX, TPA APP CON, SRQ ATCT, AMGR

CHANGES - REASONS:

- EQUIPMENT REQUIREMENT NOTES: ADDED "RADAR REQUIRED." - NOTE MOVED FROM PROCEDURAL DATA NOTES AND IAW 8260.46J, APPENDIX D, SECTION 2.2.F.
- TAKEOFF OBSTACLE NOTES: REMOVED OBSTACLES AND ADDED "SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)." - NOT REQUIRED FOR SID AND IAW 8260.46J, APPENDIX D, SECTION 2.2.I.
- MSA: ADDED "MSA FROM SRQ VOR/DME, 2800." - IAW 8260.46J, APPENDIX D, SECTION 2.2.K.
- ADDITIONAL FLIGHT DATA: ADDED "AIRPORT MV: SRQ W05/2010" - IAW MEMO 283 DATED 07/15/2022.
- AIRPORTS SERVED: UPDATED INFORMATION TO INCLUDE AIRPORT ID "SRQ" - IAW 8260.46J, APPENDIX D, SECTION 2.2.N.
- REMARKS: DELETED "SARASOTA SIX AMENDMENT DOES NOT SATISFY PERIODIC REVIEW REQUIREMENTS." AND ADDED "ABBREVIATED AMENDMENT" - IAW 8260.46J, APPENDIX D, SECTION 2.2.Q.
- REMARKS: ADDED "MSA OBTAINED FROM PUBLISHED APPROACH PROCEDURE AT SRQ." - IAW 8260.46J, APPENDIX D, SECTION 2.2.Q.
- FIXES AND/OR NAVAIDS: DELETED "CTY VORTAC, CYY VOR/DME, GNV VORTAC, TAY VORTAC"- VOR MON AND REQUESTED BY ATC.

