

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES											MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW35L CLIMB TO 4000 DIRECT SACRO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, LT, 185.47 INBOUND. CHART FAS OBST: 233 POLE 282319N/0811700W DISTANCE TO THLD FROM 200 HAT: 0.45 NM. WAAS CHANNEL # 45813 REFERENCE PATH ID: W35B CHART IN PLANVIEW: EXECUTIVE AIRPORT. CHART CIRCLING ICON. LTP HAE: -1.5 M							
ODDEL (IAF)		FOBUK (NOPT) (FB)		320.89 / 9.27			4000									
FOBUK (IF/IAF)		FITEM (FB)		005.47 / 3.15			3000									
FITEM		SPURR (FB)		005.47 / 4.41			1600									
SPURR (FAF)		AMICI/1.24 NM TO RW35L (FB)		005.47 / 3.33												
AMICI/1.24 NM TO RW35L		RW35L (MAP) (FO)		005.47 / 1.24												
RW35L (MAP)		288 MSL		005.47												
288 MSL		SACRO (FO)					4000									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S FOBUK, RT, 005.47 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC: 005.47 FAF: SPURR DIST FAF TO MAP: 4.57 THLD: 4.57 4. MIN. ALT: FOBUK 4000, FITEM 3000, SPURR 1600, AMICI/1.24 NM TO RW35L 540* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1600 GS ALT AT: SPURR 1600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 56.8 34:1 IS CLEAR 8. MSA FROM: RW35L 3000											MAG VAR: 6W		EPOCH YEAR: 2015			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD							
CATEGORY ==>		A		B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	288	2400	200	288	2400	200	288	2400	200	288	2400	200				
LNAV/VNAV DA	407	2700	319	407	2700	319	407	2700	319	407	2700	319				
LNAV MDA	500	2400	412	500	2400	412	500	4000	412	500	4000	412				
CIRCLING	740	1	644	740	1	644	740	1 3/4	644	740	2	644				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -1C (31F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: BRIGHT LIGHTS ON HIGHWAY MIDWAY BETWEEN RWY 35L AND RWY 35R MAY BE MISTAKEN FOR RUNWAY LIGHTS. (SEE FORM 8260-10)																
CITY AND STATE		ELEVATION: 96 TDZE: 88		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:						
ORLANDO, FL		AIRPORT NAME:		ORLANDO INTL		RNAV (GPS) RWY 35L, AMDT 1 5 FEBRUARY 2015				AMDT: ORIG-B						
										DATED 09/20/2012						



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT ODDEL ON V267-295-531 SOUTHBOUND, AND V441 EASTBOUND.

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 35R, AND RWY 36L, OR RWY 35R AND RWY 36R.

CHART NOTE: LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS.

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.

***LNAV ONLY**

CHART NOTE: FOR INOPERATIVE ALSF-2, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO RVR 5100 AND LNAV CAT C/D VISIBILITY TO RVR 6000.



CITY AND STATE ORLANDO, FL	ELEVATION: 96 TDZE: 88 AIRPORT NAME: ORLANDO INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35L, AMDT 1 5 FEBRUARY 2015	SUP:
				AMDT: ORIG-B
				DATED: 09/20/2012

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KMCO
RUNWAY	RW35L
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35B
LTP/FTP LATITUDE	282429.1950N
LTP/FTP LONGITUDE	0811744.1335W
LTP/FTP ELLIPSOIDAL HEIGHT	-00015
FPAP LATITUDE	282608.2025N
FPAP LONGITUDE	0811745.1655W
THRESHOLD CROSSING HEIGHT (TCH)	00056.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

B40D977C

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00264
FPAP ORTHOMETRIC HEIGHT	+00264

QUALITY
4
CHECKED

CITY AND STATE

ORLANDO, FL

ELEVATION: 96

TDZE: 88

AIRPORT NAME:

ORLANDO INTL

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35L, AMDT 1

5 FEBRUARY 2015

SUP:

AMDT: ORIG-B

DATED: 09/20/2012

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

	1										2										3										4										5										6										7										8										9										0										1										2										3									
MSA	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100																														

CITY AND STATE ORLANDO, FL	ELEVATION: 96 TDZE: 88 AIRPORT NAME: ORLANDO INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 35L, AMDT 1 5 FEBRUARY 2015	SUP: CHECKED
				AMDT: ORIG-B
				DATED: 09/20/2012

SUSAP KMCOK7SRW35LK7PG018018003025M

CITY AND STATE ORLANDO, FL	ELEVATION: 96	TDZE: 88	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 35L, AMDT 1 5 FEBRUARY 2015	SUP:
	AIRPORT NAME: ORLANDO INTL	AMDT:			
	DATED: 09/20/2012				

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	FOBUK	FOBUK	010	IAF	HF	R	FO		005.5 (359.5T)	004.0	AA 04000	
	ODDEL	ODDEL	010	IAF	IF		FB					
	ODDEL	FOBUK	020		TF		FB	1.0	320.9 (314.9T)	009.3	AA 04000	
		FOBUK	010	FACF	IF		FB				AA 04000	
		FITEM	011	SDF	TF		FB	0.5	005.5 (359.5T)	003.2	AA 03000	
		SPURR	020	FAF	TF		FB	0.5	005.5 (359.5T)	004.4	AA 01600	
		AMICI	021	SDF	TF		FB	0.3	005.5 (359.5T)	003.3	AA 00540 GS 00541	
		RW35L	030	MAP	TF		FO	0.3	005.5 (359.5T)	001.2	AT 00144	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		005.5 (359.5T)		AA 00288	
		SACRO	050		DF		FO				AA 04000	
		SACRO	060		HM	L	FO		185.5 (179.5T)	004.0	AA 04000	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		AMICI	N282314.33		W0811743.35		N2823.239		W08117.723			
		FITEM	N281528.58		W0811738.48		N2815.476		W08117.641			
		FOBUK	N281219.08		W0811736.50		N2812.318		W08117.608			
		ODDEL	N280545.51		W0811010.24		N2805.759		W08110.171			
		SACRO	N284434.45		W0811756.78		N2844.574		W08117.946			
		SPURR	N281954.09		W0811741.26		N2819.902		W08117.688			
		RW35L	N282429.20		W0811744.13		N2824.487		W08117.736			
RUNWAY DATA		RWY	THRESHOLD ELEVATION		TCH							
		RW35L	00087		57							

CITY AND STATE ORLANDO, FL	ELEVATION: 96	TDZE: 88	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 35L, AMDT 1 5 FEBRUARY 2015	SUP:
	AIRPORT NAME: ORLANDO INTL		RNAV		AMDT: ORIG-B
					DATED: 09/20/2012