

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE UKIAH ALTIMETER SETTING AND INCREASE ALL MDA 260 FEET.

TAA

	FROM	TO	ALT
1.	055/30 CW 235/30	055/10 CW 235/10	9800
2.	055/10 CW 235/10	NEAPO (IF/IAF) (FO)	6700
3.	235/30 CW 325/30	XUGME (IAF) (FB)	9700
4.	325/30 CW 055/30	ZONJO (IAF) (FB)	6500

QUALITY
CHECKED

CITY AND STATE
WILLITS, CA

ELEVATION: 2063 TDZE: 2063
AIRPORT NAME:
ELLS FIELD-WILLITS MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 16, AMDT 1
18 NOV 2010

SUP:
AMDT: ORIG-A
DATED: 11/23/2006

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 028 K2FR16	ANEAP010NEAPOK2EA0EE	AR	HF				14490050		+ 06000	18000			B JS
SUSAP 028 K2FR16	AXUGME 010XUGMEK2EA0E	A	IF							18000			B JS
SUSAP 028 K2FR16	AXUGME 020NEAPOK2EA0EE	B	010TF				23500080		+ 06000				B JS
SUSAP 028 K2FR16	AZON0J 010ZON0JK2EA0E	A	IF							18000			B JS
SUSAP 028 K2FR16	AZON0J 020NEAPOK2EA0EE	B	010TF				05490050		+ 06000				B JS
SUSAP 028 K2FR16	R	010NEAPOK2EA0E	I	IF					+ 06000	18000			B JS
SUSAP 028 K2FR16	R	011ADBAWK2EA0E	S	051TF			14490041		+ 04800				B JS
SUSAP 028 K2FR16	R	020LEFORK2EA1E	F	051TF			14500030		+ 04000				B JS
SUSAP 028 K2FR16	R	020LEFORK2EA2WN			N	ALNAV							JS
SUSAP 028 K2FR16	R	030RW16 K2PG0GY	M	031TF			14500060		02103	-300			B JS
SUSAP 028 K2FR16	R	040	0	M	010CA		1450		+ 02463				B JS
SUSAP 028 K2FR16	R	050HULDIK2EA0E		010DF									B JS
SUSAP 028 K2FR16	R	060ENI K2D 0VY		010TF			1544		+ 06000				B JS
SUSAP 028 K2FR16	R	070ENI K2D 0VE	R020HM				02200050		+ 06000				B JS

QUALITY
&
CHECKED

CITY AND STATE WILLITS, CA	ELEVATION: 2063 AIRPORT NAME: ELLS FIELD-WILLITS MUNI	TDZE: 2063	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, AMDT 1 18 NOV 2010	SUP:	
					AMDT:	ORIG-A
					DATED:	11/23/2006

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

ELEVATION: 2063 TDZE: 2063
AIRPORT NAME:
ELLS FIELD-WILLITS MUNI

FACILITY
IDENTIFIER:
BNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, AMDT 1
18 NOV 2010

SUP:	
AMDT:	ORIG-A
DATED:	11/23/2006