

<b>RNAV - STANDARD</b> <b>INSTRUMENT APPROACH PROCEDURE</b> <b>TITLE 14 CFR PART 97.33</b>						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
<b>TERMINAL ROUTES</b>											<b>MISSED APPROACH</b>						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW10L  CLIMB TO 2000 DIRECT JUTAS AND ON TRACK 183.72 TO ODKEY AND ON TRACK 268.68 TO LANCH AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD S, RT, 009.00 INBOUND. CHART FAS OBST: 229 TOWER 264118N/0801046W. DISTANCE TO THLD FROM 200 HAT: 0.47 NM. CHART VDP AT 1.30 NM TO RW10L* *LNAV ONLY. WAAS CHANNEL # 97317 REFERENCE PATH ID: W10A LTP HAE: -21.4 M							
PBI VORTAC		WILBA (TF) (FO) (RNP 2.00)			279.32 / 14.06			3000									
GULLO (IAF)		WILBA (NOPT) (TF) (FB) (RNP 1.00)			099.54 / 7.00			3000									
WILBA (IF/IAF)		ZISUR (TF) (FB) (RNP 1.00)			098.67 / 7.00			2000									
ZISUR (FAF)		RW10L (MAP) (TF) (FO) (RNP 0.30)			098.73 / 6.07												
RW10L (MAP)		216 MSL (CA)			098.73												
(SEE FORM 8260-10)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W WILBA, LT, 098.67 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 098.73 FAF: ZISUR DIST FAF TO MAP: 6.07 THLD: 6.07 4. MIN. ALT: WILBA 3000, ZISUR 2000 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2000 GS ALT AT: ZISUR 2000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 51.7 20:1 IS CLEAR 34:1 IS CLEAR 8. MSA FROM: RW10L 2600																	
											MAG VAR: 6W					EPOCH YEAR: 2010	
<b>MINIMUMS</b>																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD								
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA**	216	2400	200	216	2400	200	216	2400	200	216	2400	200					
LNAV/VNAV DA	404	4000	388	404	4000	388	404	4000	388	404	4000	388					
LNAV MDA	500	2400	484	500	2400	484	500	5000	484	500	5000	484					
CIRCLING	560	1	540	560	1	540	640	1 3/4	620	680	2	660					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 43C (109F). CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). PBN REQUIREMENTS NOTE: RNP APCH CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON PBI VORTAC AIRWAY RADIALS 190 CW 359. (CONTINUED ON PAGE 2)																	
CITY AND STATE				ELEVATION: 20 TDZE: 16			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
WEST PALM BEACH, FL				AIRPORT NAME:						RNAV (GPS) Y RWY 10L, AMDT 3C				AMDT: 3B			
				PALM BEACH INTL						19 JULY 2018				DATED 10/12/2017			

QUALITY  
 9  
 CHECKED

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
216 MSL	JUTAS (DF) (FB) (RNP 1.00)		
JUTAS	ODKEY (TF) (FB) (RNP 1.00)	183.72 / 8.97	
ODKEY	LANCH (TF) (FO) (RNP 1.00)	268.68 / 6.77	2000

**NOTES, (CONT.):**

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV CATS C/D VISIBILITY TO 1 3/8 SM.  
 CHART NOTE: \*\*RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.

QUALITY  
9  
CHECKED

CITY AND STATE <b>WEST PALM BEACH, FL</b>	ELEVATION: 20 AIRPORT NAME: <b>PALM BEACH INTL</b>	TDZE: 16	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) Y RWY 10L, AMDT 3C</b> 19 JULY 2018	SUP:
					AMDT: <b>3B</b>
					DATED: <b>10/12/2017</b>

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KPBI
RUNWAY	RW10L
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W10A
LTP/FTP LATITUDE	264058.9740N
LTP/FTP LONGITUDE	0800616.9160W
LTP/FTP ELLIPSOIDAL HEIGHT	-00214
FPAP LATITUDE	264054.7435N
FPAP LONGITUDE	0800440.0135W
THRESHOLD CROSSING HEIGHT (TCH)	00051.7
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 77A7E4D9

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00049
FPAP ORTHOMETRIC HEIGHT	+00049

QUALITY  
9  
CHECKED

CITY AND STATE  WEST PALM BEACH, FL	ELEVATION: 20 AIRPORT NAME:  PALM BEACH INTL	TDZE: 16	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:  RNAV (GPS) Y RWY 10L, AMDT 3C  19 JULY 2018	SUP:
					AMDT: 3B
					DATED: 10/12/2017