

**Federal Aviation
Administration**

Transmittal Letter 21-13

April 30, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
6/17/2021	MI	Manistee	Manistee County- Blacker	1/5650	4/7/2021	RNAV (GPS) RWY 10, Orig B

AIRAC Date: 17 JUNE 2021

FDC 1/5650 MBL IAP MANISTEE COUNTY-BLACKER, MANISTEE, MI. RNAV (GPS) RWY 10, ORIG-B... CIRCLING CAT A MDA 1140/HAA 519, CAT B MDA 1200/HAA 579, CAT C MDA 1400/HAA 779, CAT D MDA 1500/HAA 879. CIRCLING CAT C VISIBILITY 2 1/4, CAT D VISIBILITY 2 3/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LUDINGTON ALTIMETER SETTING: INCREASE LPV DA TO 921 FEET AND ALL CATS VISIBILITY 1/4 SM; INCREASE LNAV/VNAV DA TO 1141 FEET AND ALL CATS VISIBILITY 1/8 SM. INCREASE ALL MDA 60 FEET AND INCREASE LNAV CAT C/D VISIBILITY 1/8 SM AND CIRCLING CAT C/D VISIBILITY 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 800-2 1/4, CAT D 900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 10, ORIG-C. 2104061637-PERM