

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

| TERMINAL ROUTES | | | | MISSED APPROACH | | | | | | | | | | | |
|--|------------|---------------------|----------|--|-----|----------------------|--------|--|---------|------------------|-----|------------|--------|-----|---------|
| FROM | TO | COURSE AND DISTANCE | ALTITUDE | | | | | | | | | | | | |
| RANDO CORIR (IF/IAF) | CORIR (FB) | 092.70 / 27.85 | 3000 | LNAV: RW26 CLIMB TO 3000 DIRECT PEBIY AND HOLD. | | | | | | | | | | | |
| | DODGE (FB) | 260.93 / 8.21 | 2700 | | | | | | | | | | | | |
| | | | | ADDITIONAL FLIGHT DATA: HOLD W, RT, 080.53 INBOUND. CHART FAS OBST: 1109 TREE 432657N/0883545W CHART 1179 TREE 432736N/0883433W. DODGE TO RW26: 3.04/34. | | | | | | | | | | | |
| 1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD E CORIR, RT, 260.93 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 260.80 FAF: DODGE DIST FAF TO MAP: 5.36 THLD: 5.36 4. MIN. ALT: CORIR 3000, DODGE 2700 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW26 2700 | | | | | | | | MAG VAR: 1W | | EPOCH YEAR: 1995 | | | | | |
| MINIMUMS | | | | | | | | | | | | | | | |
| TAKEOFF: <input type="checkbox"/> STANDARD <input checked="" type="checkbox"/> SEE FAA FORM 8260-15A FOR THIS AIRPORT | | | | ALTERNATE: N A <input type="checkbox"/> STANDARD @ <input type="checkbox"/> | | | | | | | | | | | |
| CATEGORY | A | | | B | | | C | | | D | | | E | | |
| | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA |
| LNAV MDA | 1360 | 1 | 426 | 1360 | 1 | 426 | 1360 | 1 1/4 | 426 | | NA | | | | |
| CIRCLING | 1440 | 1 | 506 | 1440 | 1 | 506 | 1440 | 1 1/2 | 506 | | NA | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| NOTES: CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY. CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE DANE COUNTY REGIONAL-TRUAX FIELD ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. | | | | | | | | | | | | | | | |
| CITY AND STATE | | | | ELEVATION: 934 TDZE: 934 | | FACILITY IDENTIFIER: | | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: | | | | SUP: | | | |
| JUNEAU, WI | | | | AIRPORT NAME: | | RNAV | | RNAV (GPS) RWY 26, ORIG MAY 10 2007 | | | | AMDT: NONE | | | |
| | | | | DODGE COUNTY | | | | | | | | DATED | | | |



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

| SEGMENT | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 |
|------------------|--------|-----|--------------|-----------|---|---|----------|---|-------|-------|------|-------|---|
| SUSAP KUNUK5FP26 | ARANDO | 010 | RANDOK5EA0E | IF | | | | | | 18000 | | G | S |
| SUSAP KUNUK5FP26 | ARANDO | 020 | CORIRK5EA0E | 020TF | | | 09270279 | + | 03000 | | | G | S |
| SUSAP KUNUK5FP26 | ARANDO | 030 | CORIRK5EA0EE | CR HF | | | 26090050 | + | 03000 | | | G | S |
| SUSAP KUNUK5FP26 | P | 010 | CORIRK5EA0E | I IF | | | | + | 03000 | 18000 | | G | S |
| SUSAP KUNUK5FP26 | P | 020 | DODGEK5EA0E | F 051TF | | | 26090082 | + | 02700 | | RW26 | K5PGG | S |
| SUSAP KUNUK5FP26 | P | 030 | RW26 K5PGOGY | M 031TF | | | 26080054 | | 00968 | | -304 | G | S |
| SUSAP KUNUK5FP26 | P | 040 | | 0 M 010CA | | | 2608 | + | 01334 | | | G | S |
| SUSAP KUNUK5FP26 | P | 050 | PEBIYK5EA0EY | 010DF | | | | + | 03000 | | | G | S |
| SUSAP KUNUK5FP26 | P | 060 | PEBIYK5EA0EY | HR020HM | | | 08050050 | + | 03000 | | | G | S |

[illegible][illegible]

| | | | | |
|----------------------------------|--|-------------------------------------|--|-----------------|
| CITY AND STATE JUNEAU, WI | ELEVATION: 934 TDZE: 934 AIRPORT NAME: DODGE COUNTY | FACILITY IDENTIFIER: RNAV | PROCEDURE NO./ AMDT NO./ EFFECTIVE DATE: RNAV (GPS) RWY 26, ORIG MAY 10 2007 | SUP: |
| | | | | AMDT: NONE |
| | | | | DATED: |



U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

| ROUTES | TRANSITION | FIX | SEQ | USE | PATH | TURN | FO/FB | RNP | MAG (TRUE) | DISTANCE | ALTITUDE |
|--------|------------|-------|-----|------|------|------|-------|-----|--------------|----------|----------|
| | RANDO | RANDO | 010 | | IF | | FB | | | | |
| | RANDO | CORIR | 020 | | TF | | FB | 2.0 | 092.7 (092T) | 027.9 | 03000 |
| | RANDO | CORIR | 030 | | HF | R | FB | | 260.9 (260T) | 005.0 | 03000 |
| | | CORIR | 010 | FACF | IF | | FB | | | | 03000 |
| | | DODGE | 020 | FAF | TF | | FB | 0.5 | 260.9 (260T) | 008.2 | 02700 |
| | | RW26 | 030 | MAP | TF | | FO | 0.3 | 260.8 (260T) | 005.4 | 00968 |

| MISSED APPROACH | FIX | SEQ | USE | PATH | TURN | FO/FB | RNP | MAG (TRUE) | DISTANCE | ALTITUDE |
|-----------------|-------|-----|-----|------|------|-------|-----|--------------|----------|----------|
| | | 040 | | CA | | FB | 1.0 | 260.8 (260T) | | 01334 |
| | PEBIY | 050 | | DF | | FO | 1.0 | | | 03000 |
| | PEBIY | 060 | | HM | R | FO | 2.0 | 080.5 (080T) | 005.0 | 03000 |

| POINT DATA | WAYPOINT | LAT IN SECS | LONG IN SECS | LAT IN MINS | LONG IN MINS |
|------------|----------|-------------|--------------|-------------|--------------|
| | CORIR | N432802.47 | W0882332.51 | N4328.041 | W08823.542 |
| | DODGE | N432635.81 | W0883438.13 | N4326.597 | W08834.636 |
| | PEBIY | N432325.65 | W0885829.05 | N4323.428 | W08858.484 |
| | RANDO | N432858.42 | W0890146.53 | N4328.974 | W08901.776 |
| | RW26 | N432538.68 | W0884152.13 | N4325.645 | W08841.869 |

| RUNWAY DATA | RWY | THRESHOLD ELEVATION | TCH |
|-------------|------|------------------------|-----|
| | RW26 | 00934 | 34 |

CITY AND STATE
JUNEAU, WI

ELEVATION: 934 TDZE: 934
 AIRPORT NAME:
 DODGE COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 26, ORIG
 MAY 10 2007

SUP:
 AMDT: NONE
 DATED:

