

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE

MISSED APPROACH

ILS: DA
LOC: 4.90 MILES AFTER PAMME OM/RADAR OR AT OBK 6.21 DME FIX

CLIMB TO 1400 THEN CLIMBING LEFT TURN TO 2700 DIRECT OBK VOR/DME AND HOLD; OR WHEN DIRECTED BY ATC, CLIMB TO 1400 THEN CLIMBING LEFT TURN TO 2200 VIA HEADING 025 FOR RADAR VECTORS.

ADDITIONAL FLIGHT DATA:
HOLD N, LT, 163.28 INBOUND.
CHART FAS OBST: 840 TOWER 421053N/0875705W

- PT R SIDE OF COURSE 340.60 OUTBOUND 2700 FT WITHIN 10 MILES OF OBK VOR/DME (IAF)
-
- FAC: 160.60 FAF: PAMME OM/RADAR DIST FAF TO MAP: 4.90 THLD: 4.90
- MIN. ALT: PAMME OM 2300
- DIST TO THLD FROM OM: 4.90 MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 1063
- MIN GS INCPT: 2300 GS ALT AT: GS INTCP OM: 2279 MM: - IM: -
- GS ANGLE: 3.00 TCH: 51.7
- MSA FROM: OBK VOR/DME 090-180 3400, 180-090 2600

MAG VAR: 2W

EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM	8260-15A	FOR THIS AIRPORT	ALTERNATE: N A			ILS: STANDARD #			LOC: STANDARD @			
CATEGORY ==>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
S-ILS 16	893	3/4	250	893	3/4	250	893	3/4	250	893	3/4	250				
S-LOC 16	1140	1	497	1140	1	497	1140	1 1/4	497	1140	1 1/2	497				
CIRCLING	1140	1	493	1140	1	493	1140	1 1/2	493	1200	2	553				

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CHART PLANVIEW NOTE: RADAR REQUIRED.

CHART PROFILE NOTE: VGS1 AND ILS GLIDEPATH NOT COINCIDENT.

CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHICAGO-O'HARE INTL ALTIMETER SETTING AND

SEE 8260-10

CITY AND STATE

ELEVATION: 647 TDZE: 643

FACILITY
IDENTIFIER:
I-PWK

PROCEDURE NO./AMDT NO.:

ILS OR LOC RWY 16, AMDT 2

DEC 20 2007

SUP: ILS RWY 16

AMDT: 1

DATED 06/15/2000

CHICAGO/PROSPECT HGTS/WHEELING, IL

AIRPORT NAME:

CHICAGO EXECUTIVE

ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

INCREASE ALL DAS 22 FEET, AND ALL VISIBILITIES 1/4 MILE; INCREASE ALL MDAS 40 FEET, AND S-LOC CAT C AND D VISIBILITIES 1/4 MILE.

CITY AND STATE

CHICAGO/PROSPECT HGTS/WHEELING, IL

ELEVATION: 647 TDZE: 643

AIRPORT NAME:

CHICAGO EXECUTIVE

FACILITY
IDENTIFIER:
I-PWK

PROCEDURE NO./AMDT NO.:

ILS OR LOC RWY 16, AMDT 2

DEC 20 2007

SUP: ILS RWY 16

AMDT: 1

DATED: 06/15/2000